



Electronic parallel ignitor for HID lamp circuits

SI 52

HID ignitors for parallel systems


Product data

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Wiring	
Connector Type	Screw
Temperature	
Ambient temperature range	-20 °C to 75 °C
T-Case Maximum (Max)	80 °C
Mechanical and Housing	
Housing	Akulon S223

Approval and Application	
Approval Marks	CE marking
Product Data	
Order product name	SI 52
Full product name	SI 52
Full product code	871016303343300
Order code	913710010814
Material Nr. (12NC)	913710010814
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163148595
Numerator - Packs per outer box	48
EAN/UPC - Case	8710163033433

Electronic parallel ignitor for HID lamp circuits

Dimensional drawing



Product	C1	A1	A2	B1	D1
SI 52	38.5 mm	85.5 mm	65.0 mm	41.5 mm	4.3 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 30 - data subject to change