



Electronic parallel ignitor for HID lamp circuits

SI 51 Plus

HID ignitors for parallel systems

Product data


| Operating and Electrical | |
|---------------------------|-----------------|
| Input Voltage | 220 to 240 V |
| Line Frequency | 50 to 60 Hz |
| Input Frequency | 50 to 60 Hz |
| | |
| Wiring | |
| Connector Type | Screw |
| | |
| Temperature | |
| Ambient temperature range | -20 °C to 75 °C |
| T-Case Maximum (Max) | 80 ℃ |
| | |
| Mechanical and Housing | |
| Housing | Akulon S223 |
| | |

| CE marking ENEC certificate | | |
|-----------------------------|--|--|
| | | |
| SI 51 Plus | | |
| SI 51 Plus | | |
| 697013372887100 | | |
| 913710011113 | | |
| 913710011113 | | |
| 1 | | |
| 6970133728871 | | |
| 48 | | |
| 6970133728888 | | |
| | | |

Datasheet, 2023, April 15 data subject to change

Electronic parallel ignitor for HID lamp circuits

Dimensional drawing



| Product | C1 | A1 | A2 | B1 | D1 |
|------------|---------|---------|---------|---------|--------|
| SI 51 Plus | 38.5 mm | 85.5 mm | 65.0 mm | 41.5 mm | 4.3 mm |



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.