

Electronic digital control ignitor for HID lamp circuits

SU 42-S

HID ignitors for series systems

Product data

Operating and Electrical	
Input Voltage	220 to 230 V
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz

Wiring	
Connector Type	Screw

Temperature	
T-Case Maximum (Max)	105 °C


Mechanical and Housing	
Housing	PC UL94V-2

Approval and Application	
Approval Marks	CE marking China Quality Certificate CB Certificate

Product Data	
Order product name	SU 42-S
Full product name	SU 42-S
Full product code	697013372897000
Order code	913710016213
Material Nr. (12NC)	913710016213
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6970133728970
Numerator - Packs per outer box	20
EAN/UPC - Case	6970133728987

Electronic digital control ignitor for HID lamp circuits

Dimensional drawing



Product	A2	C1	A1	B1
SU 42-S	63.4 mm	34 mm	96 mm	45 mm

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.