

HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

BSN 70L 302I

The HID Basic Semi-Parallel ballast is an impregnated (HID standard) electromagnetic copper/iron ballast for use with an external ignitor for HID lamps.


Product data

General Information	
Application Code	L302 I
Operating and Electrical	
Input Voltage	230 V
Input Frequency	50 Hz
Power Factor 100% Load (Min)	0.85
Mains Voltage Performance (AC)	-8% - +6%
Mains Voltage Safety (AC)	-10% - +10%
Input Current with PF Correction	0.45 A
Input Current without PF Correction	0.98 A
Power Factor without PF Compensation (Nom)	0.35
Power Losses (Nom)	13.5 W
Wiring	
Connector Type	Screw
System characteristics	
Rated Ballast-Lamp Power	70 W

Temperature	
T-Winding (Max)	130 °C
Delta-T Normal Conditions	70 °C
Approval and Application	
Approval Marks	CE marking
Product Data	
Full product code	871016303163730
Order product name	BSN 70L 302I
EAN/UPC - Product	8710163148526
Order code	913710104750
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	913710104750
Net Weight (Piece)	1.100 kg

HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

Dimensional drawing



Product	D1	C1	A1	A2	B1
BSN 70L 302I	6.2 mm	51.5 mm	117.0 mm	102 mm	57.1 mm

BSN 70 L302 I

