PHILIPS

Lighting



ROVR

ROVR ELE DIMMING BALLAST (4) F32T8 120-277V

Philips Advance ROVR ballasts reflect the latest approach to controlling fluorescent lighting. Rather than simply responding to instructions from control components, ROVR ballasts enable twoway communication, and have the ability to dim and switch individual ballasts through the control signal. These features allow for virtually unlimited design flexibility while creating sustainable lighting systems. This two-way communication is made possible through the industry-standard digital communication protocol known as DALI (Digital Addressable Lighting Interface). This protocol allows ROVR ballasts to provide users with operational data while controlling the output of individual luminaires. This fully supports sustainable design principles such as daylight harvesting and occupancy sensors while enabling a proactive response to maintenance concerns.

Product data

General Information	
Lamp Type	F32T8
Number of Lamps	4 piece/unit
Ballast Type	Dimmable Fluorescent
Base Model	IDA4S32
Suitable For Outdoor Use	Yes
Automatic Restart	Yes

Operating and Electrical	
Input Voltage	120 to 277 V
Input Frequency	50 to 60 Hz
Total Harmonic Distortion USA	10 %
Ignition Method	Programmed Start
Crestfactor (Nom)	1.7
Ignition Time (Nom)	1.5 s
Ballast Factor (Max)	0.88
Ballast Factor (Min)	0.03
Power Factor (Nom)	0.99
Input Current (Max)	0.77 A
Input Current (Min)	0.42 A
Input Power (Max)	116 W
Input Power (Min)	25 W
Rated Lamp Power	32 W

Wiring	
Color Input Terminals	Black, White and Purple
Color Output Terminals	RED, YEL, BLU, BLU/WHT & BRN
Wire Striplength	0.375 mm
Control Wire Gauge	18AWG
Lamp Connection	Series
Wire Length by Color	No wires
Wire Gauge (Nom)	18AWG mm

ROVR

Wire Type	Solid
Remote Wiring Configuration Allowed	No
Tandem Wiring Configuration Allowed	No
Through Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	No Remote
Max Ballast-Lamp Distance Tandem Wiring	No Tandem
Max Ballast-Lamp Distance Through Wiring	Yellow & Brown = 4'
Connector Type	Poke-In

Temperature

T-Case Maximum (Nom)	70 °C

Mechanical and Housing

Housing Material	Metal
Housing	D
Housing Dimensions	16.7" x 1.18" x 1.0"


Approval and Application

EMC Immunity Standard	FCC Consumer
Approval Marks	CSA certificate UL certificate CEC Listing CEE Rated NEMA Premium RoHS Compliant
Hum And Noise Level	A
UL Recognized	No

Product Data

Order product name	ROVR ELE DIMMING BALLAST (4) F32T8 120-277V
EAN/UPC - Product	781087034507
Order code	913710212302
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	913710212302
Net Weight (Piece)	500.000 g

Dimensional drawing



ELE DIMMING BALLAST (4) F32T8 120-277V

Product	A1	A2	B1	C1
ROVR IDA4S3235M	16.70 in	16.34 in	1.18 in	1.00 in

© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.