



Mark 10 Powerline

MARK 10 POWERLINE ELE DIM BALLAST (1) 18W CFL (4-PIN) 120V

For companies looking to make their fixed-output linear T8, 4-pin CFL, and T5/HO fluorescent systems more cost effective and sustainable, Mark 10 Powerline ballasts provide an easy solution without the need for additional control leads. Simply, (1) replace the ballast, (2) replace the switch, (3) dim the lights, that is all it takes. It's that easy to bring the convenience and flexibility of fluorescent dimming to conference rooms, private offices, auditoriums, architectural cove lighting — anywhere dimming is required.

Product data

General Information				
Lamp Type	CFQ18W/G24Q			
Number of Lamps	1 piece/unit			
Ballast Type	Dimmable Fluorescent			
Base Model	REZ1Q18M2LD			
Suitable For Outdoor Use	Yes			
Automatic Restart	Yes			
Operating and Electrical				
Input Voltage	120 V			
Input Frequency	60 Hz			
Total Harmonic Distortion USA	10 %			
Ignition Method	Programmed Start			
Crestfactor (Nom)	1.6			
Ignition Time (Nom)	1.5 s			
Ballast Factor (Max)	1			
Ballast Factor (Min)	0.05			
Power Factor (Nom)	0.99			
Input Current (Nom)	0.18 A			

Input Power (Max)	22 W	
Input Power (Min)	7 W	
Rated Lamp Power	18 W	
Wiring		
Color Input Terminals	Black and White	
Color Output Terminals	RED & BLU	
Wire Striplength	0.375 mm	
Control Wire Gauge	NA	
Lamp Connection	Series	
Wire Length by Color	No wires	
Wire Gauge (Nom)	18AWG mm	
Wire Type	Solid	
Remote Wiring Configuration Allowed	No	
Tandem Wiring Configuration Allowed	No	
Through Wiring Configuration Allowed	No	
Max Ballast-Lamp Distance Remote Wiring	No Remote	
Max Ballast-Lamp Distance Tandem Wiring	NA	
Max Ballast-Lamp Distance Through Wiring NA		


Datasheet, 2019, February 12 data subject to change

Mark 10 Powerline

Connector Type	Poke-In
Temperature	
T-Case Maximum (Nom)	70 °C
Mechanical and Housing	
Housing Material	Metal
Housing	M2
Housing Dimensions	4.98" x 3.0" x 1.29"
Approval and Application	
EMC Immunity Standard	FCC Consumer
Approval Marks	CSA certificate UL certificate CEC Listing
	RoHS Compliant

Hum And Noise Level	A			
UL Recognized	No			
Product Data				
Order product name	MARK 10 POWERLINE ELE DIM BALLAS			
	(1) 18W CFL (4-PIN) 120V			
EAN/UPC - Product	781087115138			
Order code	913710231102			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	20			
Material Nr. (12NC)	913710231102			
Net Weight (Piece)	0.309 kg			

Dimensional drawing



ELE DIM BALLAST (1) 18W CFL (4-PIN) 120V

Product	A1	A2	B1	C1
MARK 10 POWERLINE REZ1Q18M2LD35M	4.55 in	4.20 in	3.00 in	1.29 in



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.