# **PHILIPS** Lighting



## Mark 10 Powerline

### MARK 10 POWERLINE ELE DIM BALLAST (1) 18W CFL (4-PIN) 277V

For companies looking to make their fixed-output linear T8, 4-pin CFL, and T5/HO fluorescent systems more cost effective and sustainable, Mark 10 Powerline ballasts provide an easy solution without the need for additional control leads. Simply, (1) replace the ballast, (2) replace the switch, (3) dim the lights, that is all it takes. It's that easy to bring the convenience and flexibility of fluorescent dimming to conference rooms, private offices, auditoriums, architectural cove lighting – anywhere dimming is required.

#### **Product data**

General Information					
Lamp Type	CFQ18W/G24Q				
Number of Lamps	1 piece/unit				
Ballast Type	Dimmable Fluorescent				
Base Model	VEZ1Q18M2LD				
Suitable For Outdoor Use	Yes				
Automatic Restart	Yes				
Operating and Electrical					
Input Voltage	277 V				
Input Frequency	60 Hz				
Total Harmonic Distortion USA	10 %				
Ignition Method	Programmed Start				
Crestfactor (Nom)	1.6				
Ignition Time (Nom)	1.5 s				
Ballast Factor (Max)	1				
Ballast Factor (Min)	0.05				
Power Factor (Nom)	0.99				
Input Current (Nom)	0.08 A				


Input Power (Max)	22 W
Input Power (Min)	7 W
Rated Lamp Power	18 W
Wiring	
Color Input Terminals	Black and White
Color Output Terminals	RED & BLU
Wire Striplength	0.375 mm
Control Wire Gauge	NA
Lamp Connection	Series
Wire Length by Color	No wires
Wire Gauge (Nom)	18AWG mm
Wire Type	Solid
Remote Wiring Configuration Allowed	No
Tandem Wiring Configuration Allowed	No
Through Wiring Configuration Allowed	No
Max Ballast-Lamp Distance Remote Wiring	No Remote
Max Ballast-Lamp Distance Tandem Wiring	NA
Max Ballast-Lamp Distance Through Wiring	NA

#### Mark 10 Powerline

Connector Type	Poke-In			
Temperature				
T-Case Maximum (Nom)	70 °C			
Mechanical and Housing				
Housing Material	Metal			
Housing	M2			
Housing Dimensions	4.98" x 3.0" x 1.29"			
Approval and Application				
EMC Immunity Standard	FCC Consumer			
Approval Marks	CSA certificate UL certificate CEC Listing			
	RoHS Compliant			

Hum And Noise Level	A			
UL Recognized	No			
Product Data				
Order product name	MARK 10 POWERLINE ELE DIM BALLAST			
	(1) 18W CFL (4-PIN) 277V			
EAN/UPC - Product	781087115152			
Order code	913710250202			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	20			
Material Nr. (12NC)	913710250202			
Net Weight (Piece)	323.000 g			

#### **Dimensional drawing**



Product	AI	AZ	ы	CI
MARK 10 POWERLINE VEZ1Q18M2LD35M	4.55 in	4.20 in	3.00 in	1.29 in

44 43

**D1** 



- - -

© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, February 12 - data subject to change