



Mark 10 Powerline

MARK 10 POWERLINE ELE DIM BALLAST (1) 40W CFL (4-PIN) 277V

For companies looking to make their fixed-output linear T8, 4-pin CFL, and T5/HO fluorescent systems more cost effective and sustainable, Mark 10 Powerline ballasts provide an easy solution without the need for additional control leads. Simply, (1) replace the ballast, (2) replace the switch, (3) dim the lights, that is all it takes. It's that easy to bring the convenience and flexibility of fluorescent dimming to conference rooms, private offices, auditoriums, architectural cove lighting — anywhere dimming is required.

Product data

General Information					
Lamp Type	FT40W/2G11				
Number of Lamps	1 piece/unit				
Ballast Type	Dimmable Fluorescent				
Base Model	VEZ1TTS40SC				
Suitable For Outdoor Use	Yes				
Automatic Restart	Yes				
Operating and Electrical					
Input Voltage	277 V				
Input Frequency	60 Hz				
Max THD	10 %				
Starting Method	Programmed Start				
Lamp Current Crest Factor (Nom)	1.7				
Ignition Time (Nom)	1.5 s				
Ballast Factor (Max)	1				
Ballast Factor (Min)	0.05				
Power Factor (Nom)	0.99				
Input Current (Operating) (Nom)	0.15 A				

Input Power (Max)	41 W			
Input Power (Min)	10 W			
Rated Lamp Watts	40 W			
Wiring				
Color Input Terminals	No terminals			
Color Output Terminals	No terminals			
Wire Striplength	0.50/0.375 mm			
Control Wire Gauge	NA			
Lamp Connection	Series			
Wire Length by Color	See data sheet			
Wire Gauge (Nom)	18AWG mm			
Wire Type	Solid			
Remote Wiring Configuration Allowed	Yes			
Tandem Wiring Configuration Allowed	No			
Through Wiring Configuration Allowed	No			
Max Ballast-Lamp Distance Remote Wiring	6'			
Max Ballast-Lamp Distance Tandem Wiring	NA			
Max Ballast-Lamp Distance Through Wiring NA				


Datasheet, 2019, February 12 data subject to change

Mark 10 Powerline

Connector Type	No connector			
Temperature				
T-Case Maximum (Nom)	70 °C			
Mechanical and Housing				
Housing Material	Metal			
Housing	SC			
Housing Dimensions	9.5" x 1.7" x 1.18"			
Approval and Application				
EMC Immunity Standard	FCC Consumer			
Approbation Marks	CSA certificate UL certificate CEC Listing			
	RoHS Compliant			

Sound Rating	A			
UL Recognized	No			
Product Data				
Order product name	MARK 10 POWERLINE ELE DIM BALLAST			
	(1) 40W CFL (4-PIN) 277V			
EAN/UPC - Product	781087117033			
Order code	VEZ1TTS40SC35M			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	20			
Material Nr. (12NC)	913710250602			
Net Weight (Piece)	377.000 g			

Dimensional drawing



Product	A1	A2	B1	C1
MARK 10 POWERLINE VEZ1TTS40SC35M	9.5 in	8.90 in	1.7 in	1.18 in



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.