



Core & Coil (71A) LPS

CORE & COIL HID LPS BAL 135/180W L73/74 347/480V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information	
ANSI Code	L74
Lamp Type	180W LPS
Number of Lamps	1 piece/unit
Circuit Type	HX-HPF
Ballast Type	Magnetic HID
Base Model	71A07F0
Core Size	4 1/4 x 5 3/4 (2 coil)
Suitable For Outdoor Use	Yes
Capacitor Value	16 MFD
Capacitor Catalog Number	7C160P40
Capacitor Requirements	330V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval Dimensions	1.75 in
Capacitor Height	3.75 in
Automatic Restart	No
Operating and Electrical	
Input Voltage	347/480 V
Input Frequency	60 Hz
Inp. Current (Open Circuit)	1.82/1.33 A
Input Current (Starting)	0.76/0.54 A
Input Current (Short Circuit)	0.26-0.4/0.19-0.29 A

Secondary Short Circuit Current	0.96-1.17 A	
Constant Wattage Deviation	10%	
Ballast Factor (Nom)	1	
Power Factor (Nom)	0.90	
Nominal Open Circuit Voltage	690 V	
Input Current (Operating) (Nom)	0.62/0.45 A A	
Input Power (Nom)	213 W	
Rated Lamp Watts	180 W	
Wiring		
Wire Striplength	0.5 mm	
Wire Length by Color	12"	
Wire Type	Stranded	
Remote Wiring Configuration Allowed	Yes	
Max Ballast-Lamp Distance Remote Wiring Determined by AWG used		
Recommended Fuse Value	5/4 A	
Approval and Application		
Open Circuit Voltage Test (Volts)	620-755 V	
Approbation Marks	ULR CSA certificate RoHS Compliant	
Temperature Marking	A/A	
UL Recognized	Yes	
Hipot Test (1 Minute)	2000 V	


Datasheet, 2019, February 12 data subject to change

Core & Coil (71A) LPS

Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029A
Product Data	
Order product name	CORE & COIL HID LPS BAL 135/180W
	L73/74 347/480V C&C
EAN/UPC - Product	781087119914

Order code	71A07F0510D
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	3
Material Nr. (12NC)	913710460602
Net Weight (Piece)	7.834 kg

Dimensional drawing



LPS BAL 135/180W L73/74 347/480V C&C

