



Core & Coil (71A) MH ~GT~ 450W

CORE & COIL HID MH BAL 1000W M141 QUAD C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information				
ANSI Code	M141			
Lamp Type	1000W MH			
Number of Lamps	1 piece/unit			
Circuit Type	SUPER-CWA			
Ballast Type	Magnetic HID			
Base Model	71A6593			
Core Size	4 1/4 x 6 (2 Coil)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI571-H5			
Ignitor Temperature Rating	105°C			
Capacitor Value	24 MFD			
Capacitor Catalog Number	MD2409000			
Capacitor Requirements	480V			
Capacitor Temperature Rating	90°C			
Capacitor Diameter/Oval Dimensions	1.75 in			
Capacitor Height	3.9 in			
Automatic Restart	No			

Operating and Electrical					
Input Voltage	120/208/240/277 V				
Input Frequency	60 Hz				
Inp. Current (Open Circuit)	4.5/2.7/2.3/2.2 A				
Input Current (Starting)	7.8/4/3.7/3.2 A				
Input Current (Short Circuit)	5.6-8.6/3.2-4.8/2.8-4.3/2.4-3.75 V				
Secondary Short Circuit Current	5.2-6.4 A				
Constant Wattage Deviation	12%				
Ballast Factor (Nom)	1				
Power Factor (Nom)	0.90				
Nominal Open Circuit Voltage	430 V				
Input Current (Operating) (Nom)	9/5.2/4.5/3.9 A A				
Input Power (Nom)	1080 W				
Rated Lamp Watts	1000 W				
Wiring					
Wire Striplength	0.5 mm				
Wire Length by Color	12"				
Wire Type	Stranded				
Remote Wiring Configuration Allowed	Yes				


Datasheet, 2019, February 12 data subject to change

Core & Coil (71A) MH ~GT~ 450W

Max Ballast-Lamp Distance Remote Wiring	5'				
Recommended Fuse Value	20/15/10/10 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	385-475 V				
Approbation Marks	ULR RoHS Compliant				
Temperature Marking	D/B/B/B				
UL Recognized	Yes				
Hipot Test (1 Minute)	1500 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				
UL Temperature Code	1029D				

Product Data					
Order product name	CORE & COIL HID 71A6593510				
EAN/UPC - Product	781087110256				
Order code	71A6593510				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	2				
Material Nr. (12NC)	913710474902				
Net Weight (Piece)	10.489 kg				

Dimensional drawing



MH BAL 1000W M141 QUAD C&C

Product	C 1	C2	A1	A2	А3	B1	B2
CORE & COIL HID 71A6593510	4.5 in	2.8 in	6 in	5.4 in	4.4 in	4.3 in	3.9 in

