



Core & Coil (71A) HPS ~LT~ 200W

CORE & COIL HID HPS BAL 150W S55 120V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

| General Information | | | | |
|------------------------------------|----------------|--|--|--|
| ANSI Code | S55 | | | |
| Lamp Type | 150W HPS | | | |
| Number of Lamps | 1 piece/unit | | | |
| Circuit Type | R-HPF | | | |
| Ballast Type | Magnetic HID | | | |
| Base Model | 71A8107 | | | |
| Core Size | 2 5/8 x 2 3/16 | | | |
| Suitable For Outdoor Use | Yes | | | |
| Ignitor Catalog Number | LI551-H4 | | | |
| Ignitor Temperature Rating | 105°C | | | |
| Capacitor Value | 55 MFD | | | |
| Capacitor Catalog Number | 7C550P12RA | | | |
| Capacitor Requirements | 120V | | | |
| Capacitor Temperature Rating | 105°C | | | |
| Capacitor Diameter/Oval Dimensions | 1.75 in | | | |
| Capacitor Height | 3.75 in | | | |
| Automatic Restart | No | | | |
| | | | | |
| Operating and Electrical | | | | |
| Input Voltage | 120 V | | | |
| | | | | |

| Input Frequency | 60 Hz | | |
|--|------------------|--|--|
| Inp. Current (Open Circuit) | 2.35 A | | |
| Input Current (Starting) | 2.25 A | | |
| Input Current (Short Circuit) | 1.65-2.75 A | | |
| Secondary Short Circuit Current | 3.65-5.55 A | | |
| Constant Wattage Deviation | Within Trapezoid | | |
| Ballast Factor (Nom) | 1 | | |
| Power Factor (Nom) | 0.90 | | |
| Nominal Open Circuit Voltage | 120 V | | |
| Input Current (Operating) (Nom) | 1.5 A A | | |
| Input Power (Nom) | 170 W | | |
| Rated Lamp Watts | 150 W | | |
| | | | |
| Wiring | | | |
| Wire Striplength | 0.5 mm | | |
| Wire Length by Color | 12" | | |
| Wire Type | Stranded | | |
| Remote Wiring Configuration Allowed | Yes | | |
| Max Ballast-Lamp Distance Remote Wiring 2' | | | |
| Recommended Fuse Value | 8 A | | |
| | | | |


Datasheet, 2019, February 12 data subject to change

Core & Coil (71A) HPS ~LT~ 200W

| Approval and Application | | | | | |
|-----------------------------------|---------------------------------------|--|--|--|--|
| Open Circuit Voltage Test (Volts) | 114-126 V | | | | |
| Approbation Marks | ULR CSA certificate RoHS Compliant | | | | |
| Temperature Marking | A | | | | |
| UL Recognized | Yes | | | | |
| Hipot Test (1 Minute) | 2000 V | | | | |
| Hipot Test (2 Seconds) | 2500 V | | | | |
| UL Insulation Class | H(180°C) | | | | |
| UL Temperature Code | 1029A | | | | |
| | | | | | |
| Product Data | | | | | |
| Order product name | CORE & COIL HID HPS BAL 150W S55 120V | | | | |
| | C&C | | | | |

| EAN/UPC - Product | 781087100479 |
|---------------------------------|--------------|
| Order code | 71A8107900D |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 12 |
| Material Nr. (12NC) | 913710536902 |
| Net Weight (Piece) | 2.028 kg |
| | |

Dimensional drawing



HPS BAL 150W S55 120V C&C

| Product | C1 | C2 | A1 | A2 | B1 | B2 |
|-----------------------------|--------|------|--------|--------|--------|--------|
| CORE & COIL HID 71A8107900D | 3.3 in | 2 in | 2.6 in | 2.2 in | 2.2 in | 1.8 in |

