



Core & Coil (71A) MH ~GT~ 450W

CORE & COIL HID MH BAL 1000W M47 5-TAP C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information	
ANSI Code	M47
Lamp Type	1000W MH
Number of Lamps	1 piece/unit
Circuit Type	CWA
Ballast Type	Magnetic HID
Base Model	71A6552CU
Core Size	4 1/4 x 6 (2 Coil)
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	NA
Ignitor Temperature Rating	NA
Capacitor Value	24 MFD
Capacitor Catalog Number	MD2409000
Capacitor Requirements	480V
Capacitor Temperature Rating	90℃
Capacitor Diameter/Oval	1.75 in
Dimensions	
Capacitor Height	3.9 in
Automatic Restart	No

Operating and Electrical						
Input Voltage	120/208/240/277/480 V					
Input Frequency	60 Hz					
Inp. Current (Open Circuit)	5.16/4.3/3.09/2.61/1.6 A					
Input Current (Starting)	6/2.82/3/2.3/1.53 A					
Input Current (Short Circuit)	4.35-6.52/2.16-3.24/2.04-3.06/1.8-2.71/1-1.51 V					
Secondary Short Circuit Current	4.97-6.08 A					
Constant Wattage Deviation	10%					
Ballast Factor (Nom)	1					
Power Factor (Nom)	0.90					
Nominal Open Circuit Voltage	426 V					
Input Current (Operating) (Nom)	9.05/5.6/4.7/4.07/2.36 A A					
Input Power (Nom)	1080 W					
Rated Lamp Watts	1000 W					
Wiring						
Wire Striplength	0.5 mm					
Wire Length by Color	12"					
Wire Type	Stranded					
Remote Wiring Configuration	Yes					
Allowed						


Datasheet, 2019, February 12 data subject to change

Core & Coil (71A) MH ~GT~ 450W

Max Ballast-Lamp Distance Remote	Determined by AWG used					
Wiring						
Recommended Fuse Value	22/15/12/10/6 A					
Approval and Application						
Open Circuit Voltage Test (Volts)	383-468 V					
Approbation Marks	ULR CSA certificate RoHS Compliant					
Temperature Marking	D/D/C/C/C					
UL Recognized	Yes					
Hipot Test (1 Minute)	2000 V					
Hipot Test (2 Seconds)	2500 V					
UL Insulation Class	H(180°C)					

UL Temperature Code	1029D					
Product Data						
Order product name	CORE & COIL HID MH BAL 1000W M47 5-TAP C&C					
EAN/UPC - Product	781087045442					
Order code	71A6552600					
Numerator - Quantity Per Pack	1					
Numerator - Packs per outer box	2					
Material Nr. (12NC)	913710586102					
Net Weight (Piece)	10.283 kg					

Dimensional drawing



Product	C1	C2	A1	A2	А3	B1	B2
CORE & COIL HID 71A6552600	4.7 in	3 in	6 in	5.4 in	4.4 in	4.3 in	3.9 in

