



Core & Coil (71A) MH ~GT~ 450W

CORE & COIL HID MH BAL 1000W M141 QUAD C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information					
ANSI Code	M141				
Lamp Type	1000W MH				
Number of Lamps	1 piece/unit				
Circuit Type	CWA				
Ballast Type	Magnetic HID				
Base Model	71A6591				
Core Size	4 1/4 x 4 3/4 (2 coil)				
Suitable For Outdoor Use	Yes				
Ignitor Catalog Number	LI572-H5				
Ignitor Temperature Rating	105°C				
Capacitor Value	24 MFD				
Capacitor Catalog Number	MD2409000				
Capacitor Requirements	480V				
Capacitor Temperature Rating	90°C				
Capacitor Diameter/Oval Dimensions	1.75 in				
Capacitor Height	3.9 in				
Automatic Restart	No				

Operating and Electrical					
Input Voltage	120/208/240/277 V				
Input Frequency	60 Hz				
Inp. Current (Open Circuit)	5/2.7/2.5/2.2 A				
Input Current (Starting)	7/4/3.5/3 A				
Input Current (Short Circuit)	5.3-8/3.1-4.7/2.65-4/2.3-3.5 V				
Secondary Short Circuit Current	4.9-6.1 A				
Constant Wattage Deviation	10%				
Ballast Factor (Nom)	1				
Power Factor (Nom)	0.90				
Nominal Open Circuit Voltage	415 V				
Input Current (Operating) (Nom)	9/5.2/4.5/3.9 A A				
Input Power (Nom)	1070 W				
Rated Lamp Watts	1000 W				
Wiring					
Wire Striplength	0.5 mm				
Wire Length by Color	12"				
Wire Type	Stranded				
Remote Wiring Configuration Allowed	Yes				


Datasheet, 2019, February 12 data subject to change

Core & Coil (71A) MH ~GT~ 450W

Max Ballast-Lamp Distance Remote	5'				
Wiring					
Recommended Fuse Value	20/15/10/10 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	370-460 V				
Approbation Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	A/A/A/A				
UL Recognized	Yes				
Hipot Test (1 Minute)	1500 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	N(AC200°C)				
UL Temperature Code	1029A				

Product Data			
Order product name	CORE & COIL HID MH BAL 1000W M141		
	QUAD C&C		
EAN/UPC - Product	781087035405		
Order code	71A6591500		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	2		
Material Nr. (12NC)	913710589502		
Net Weight (Piece)	9.140 kg		

Dimensional drawing



MH BAL 1000W M141 QUAD C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A6591500	5.25 in	3.32 in	4.8 in	4.4 in	4.3 in	3.9 in

