



Encapsulated Core & Coil (73B)

ENCAPSULATED CORE & COIL HID MH BAL 1000W M47 QUAD ENCAP

Where quiet performance is required, the standard open core and coil ballast is encapsulated (potted) in a cube-shaped steel can utilizing Class H (180° C) polyester compound.

Product data

General Information					
ANSI Code	M47				
Lamp Type	1000W MH				
Number of Lamps	1 piece/unit				
Circuit Type	CWA				
Ballast Type	Magnetic HID				
Base Model	73B6590				
Suitable For Outdoor Use	Yes				
Ignitor Catalog Number	NA				
Ignitor Temperature Rating	NA				
Capacitor Value	24 MFD				
Capacitor Catalog Number	MD2409100				
Capacitor Requirements	480V				
Capacitor Temperature Rating	90°C				
Capacitor Diameter/Oval Dimensions	1.75 in				
Capacitor Height	3.89999999 in				
Automatic Restart	No				
Operating and Electrical					
Input Voltage	120/208/240/277 V				

Input Frequency	60 Hz
Inp. Current (Open Circuit)	5/2.7/2.5/2.2 A
Input Current (Starting)	7/4/3.5/3 A
Input Current (Short Circuit)	5.3-8/3.1-4.7/2.7-4/2.3-3.5 A
Secondary Short Circuit Current	4.9-6.1 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Nominal Open Circuit Voltage	415 V
Input Current (Operating) (Nom)	9/5.2/4.5/3.9 A A
Input Power (Nom)	1070 W
Rated Lamp Watts	1000 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote	Determined by AWG used
Wiring	


Datasheet, 2019, February 12 data subject to change

Encapsulated Core & Coil (73B)

Recommended Fuse Value	20/15/10/10 A				
Mechanical and Housing					
Housing Material	Metal				
Housing	Encap				
Housing Dimensions	6.5" x 5.0" x 5.2"				
Approval and Application					
Open Circuit Voltage Test (Volts)	370-460 V				
Approbation Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	D/D/D/D				
Sound Rating	С				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	25000 V				

UL Insulation Class	H(180°C)				
UL Temperature Code	1029D				
Product Data					
Order product name	ENCAPSULATED CORE & COIL HID				
	73B6590500				
EAN/UPC - Product	781087051528				
Order code	73B6590500				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	1				
Material Nr. (12NC)	913710603301				
Net Weight (Piece)	6.700 kg				

Dimensional drawing



MH BAL 1000W M47 QUAD ENCAP

Product	A1	A2	А3	B1	B2	C1	D1
ENCAPSULATED CORE & COIL HID	7.75 in	7 in	6.3 in	5.9 in	2 in	4.9 in	0.25 in
73B6590500							

