



# Core & Coil (71A) MH ~GT~ 450W

# CORE & COIL HID MH BAL 1500W M48 QUAD C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

### **Product data**

General Information	
ANSI Code	M48
Lamp Type	1500W MH
Number of Lamps	1 piece/unit
Circuit Type	CWA
Ballast Type	Magnetic HID
Base Model	71A6792A
Core Size	4 1/4 x 6
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	NA
Ignitor Temperature Rating	NA
Capacitor Value	32 MFD
Capacitor Catalog Number	MD3202100
Capacitor Requirements	525V
Capacitor Temperature Rating	90°C
Capacitor Diameter/Oval	2 in
Dimensions	
Capacitor Height	3.75 in
Automatic Restart	No

Operating and Electrical	
Input Voltage	120/208/240/277 V
Input Frequency	60 Hz
Inp. Current (Open Circuit)	5.72/3.29/3.04/2.57 A
Input Current (Starting)	10.8/6.13/5.42/4.72 A
Input Current (Short Circuit)	9.1-13.6/5.22-7.83/4.56-6.84/3.96-5.95 V
Secondary Short Circuit Current	7.29-8.9 A
Constant Wattage Deviation	12%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Nominal Open Circuit Voltage	460 V
Input Current (Operating) (Nom)	13.4/7.8/6.8/5.9 A A
Input Power (Nom)	1610 W
Rated Lamp Watts	1500 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration	Yes
Allowed	


Datasheet, 2019, March 22 data subject to change

# Core & Coil (71A) MH ~GT~ 450W

Max Ballast-Lamp Distance Remote	Determined by AWG used				
Wiring					
Recommended Fuse Value	30/25/20/15 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	414-506 V				
Approbation Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	G/E/E/G				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				

UL Temperature Code	1029G
Product Data	
Order product name	CORE & COIL HID MH BAL 1500W M48 QUAD C&C
EAN/UPC - Product	781087063514
Order code	71A6792500A
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	913710652802
Net Weight (Piece)	14.193 kg

## Dimensional drawing



MH BAL 1500W M48 QUAD C&C

Product	C1	C2	A1	A2	А3	B1	B2
CORE & COIL HID MH BAL 1500W	6.7 in	4.7 in	6 in	5.4 in	4.4 in	4.3 in	3.9 in
M48 QUAD C&C							

