



Core & Coil (71A) HPS ~LT~ 200W

**CORE & COIL HID HPS BAL 70W S62 127/220V
C&C**

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information	
ANSI Code	S62
Lamp Type	70W HPS
Number of Lamps	1 piece/unit
Circuit Type	CWA
Ballast Type	Magnetic HID
Base Model	71A79H8A
Core Size	3 X 4 (2 coil)
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	LI551-J4
Ignitor Temperature Rating	105°C
Capacitor Value	32.5 MFD
Capacitor Catalog Number	7C325P30RA
Capacitor Requirements	150V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval Dimensions	1.85 in
Capacitor Height	3.7 in
Automatic Restart	No


Operating and Electrical	
Input Voltage	127/220 V
Input Frequency	60 Hz
Input Current (Open Circuit)	0.2/0.12 A
Input Current (Starting)	0.81/0.48 A
Input Current (Short Circuit)	0.68-1.13/0.4-0.66 A
Secondary Short Circuit Current	2-2.6 A
Constant Wattage Deviation	Within Trapezoid
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	108 V
Input Current (Nom)	0.8/0.47 A A
Input Power (Nom)	100 W
Rated Lamp Power	70 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes

Core & Coil (71A) HPS ~LT~ 200W

Max Ballast-Lamp Distance Remote Wiring 2'	
Recommended Fuse Value	2/2 A
Approval and Application	
Open Circuit Voltage Test (Volts)	95-115 V
Approval Marks	ULR NOM certificate RoHS Compliant
Temperature Marking	B/C
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029C

Product Data	
Order product name	CORE & COIL HID HPS BAL 70W S62 127/220V C&C
EAN/UPC - Product	781087071250
Order code	913710655909
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	913710655909
Net Weight (Piece)	2.255 kg

Dimensional drawing



HPS BAL 70W S62 127/220V C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID HPS BAL 70W S62 127/220V C&C	3.36 in	1.75 in	3.9 in	3.5 in	2.8 in	2.4 in

