



Core & Coil (71A) MH 175W - 450W

CORE & COIL HID MH BAL 175W M137/M152 QUAD C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information	
ANSI Code	M137-M152
Lamp Type	175W MH
Number of Lamps	1 piece/unit
Circuit Type	SUPER-CWA
Ballast Type	Magnetic HID
Base Model	71A5593EE
Core Size	3 X 4 (2 coil)
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	LI533-H4
Ignitor Temperature Rating	105°C
Capacitor Value	11 MFD
Capacitor Catalog Number	7C110M40
Capacitor Requirements	370V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval	1.65 in
Dimensions	
Capacitor Height	3.75 in
Automatic Restart	No


Operating and Electrical						
Input Voltage	120/208/240/277 V					
Input Frequency	60 Hz					
Input Current (Open Circuit)	2.0/1.16/1.15/0.85 A					
Input Current (Starting)	0.5/0.28/0.22/0.2 A					
Input Current (Short Circuit)	0.4-0.6/0.23-0.34/0.17-0.26/0.16-0.25 A					
Secondary Short Circuit Current	1.6-1.96 A					
Constant Wattage Deviation	10%					
Ballast Factor (Nom)	1					
Power Factor (Nom)	0.90					
Open Circuit Voltage	285 V					
Input Current (Nom)	1.78/1.08/0.89/0.76 A A					
Input Power (Nom)	208 W					
Rated Lamp Power	175 W					
Wiring						
Wire Striplength	0.5 mm					
Wire Length by Color	12"					
Wire Type	Stranded					

Core & Coil (71A) MH 175W - 450W

Remote Wiring Configuration	Yes
Allowed	
Max Ballast-Lamp Distance	2'
Remote Wiring	
Recommended Fuse Value	5/3/3/2 A
Approval and Application	
	250, 200.14
Open Circuit Voltage Test (Volts)	250-300 V
Approval Marks	ULR CSA certificate EISA RoHS Compliant
Approval Marks	ULR CSA certificate EISA RoHS Compliant
Approval Marks Temperature Marking	ULR CSA certificate EISA RoHS Compliant A/A/A/A
Approval Marks Temperature Marking UL Recognized	ULR CSA certificate EISA RoHS Compliant A/A/A/ Yes
Approval Marks Temperature Marking UL Recognized Hipot Test (1 Minute)	ULR CSA certificate EISA RoHS Compliant A/A/A/A Yes 2000 V

UL Temperature Code	1029A
Product Data	
Order product name	CORE & COIL HID MH BAL 175W M137/M152 QUAD
	C&C
EAN/UPC - Product	781087072059
Order code	913710664402
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	913710664402
Net Weight (Piece)	4.781 kg

Dimensional drawing



MH BAL 175W M137/M152 QUAD C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID MH BAL 175W M137/	4.41 in	3.20 in	3.9 in	3.5 in	2.8 in	2.4 in
M152 QUAD C&C						



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, March 22 - data subject to change