



## Core & Coil (71A) MH 175W - 450W

# CORE & COIL HID MH BAL 200W M136 480V/120T C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information	
ANSI Code	M136
Lamp Type	200W MH
Number of Lamps	1 piece/unit
Circuit Type	SUPER-CWA
Ballast Type	Magnetic HID
Base Model	71A5642TEE
Core Size	3 X 4 (2 coil)
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	LI533-H4
Ignitor Temperature Rating	105°C
Capacitor Value	15 MFD
Capacitor Catalog Number	7C150M33
Capacitor Requirements	330V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval Dimensions	1.65 in
Capacitor Height	3.75 in
Automatic Restart	No

Operating and Electrical	
Input Voltage	480/120T V
Input Frequency	60 Hz
Inp. Current (Open Circuit)	0.5 A
Input Current (Starting)	0.18 A
Input Current (Short Circuit)	0.14-0.22 A
Secondary Short Circuit Current	1.9-2.3 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Nominal Open Circuit Voltage	240 V
Input Current (Operating) (Nom)	0.5 A A
Input Power (Nom)	232 W
Rated Lamp Watts	200 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes


Datasheet, 2019, February 12 data subject to change

### Core & Coil (71A) MH 175W - 450W

Max Ballast-Lamp Distance Remote Wiring 2'		
Approval and Application		
Open Circuit Voltage Test (Volts)	225-265 V	
Approbation Marks	ULR CSA certificate EISA RoHS Compliant	
Temperature Marking	А	
UL Recognized	Yes	
Hipot Test (1 Minute)	2000 V	
Hipot Test (2 Seconds)	2500 V	
UL Insulation Class	H(180°C)	
UL Temperature Code	1029A	

Product Data	
Order product name	CORE & COIL HID MH BAL 200W M136
	480V/120T C&C
EAN/UPC - Product	781087070321
Order code	71A5642500DTEE
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	913710665302
Net Weight (Piece)	4.269 kg

#### Dimensional drawing



MH BAL 200W M136 480V/120T C&C

