



## Core & Coil (71A) MH 175W - 450W

# CORE & COIL HID MH BAL 400W M135/155 480V/120T C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information		
ANSI Code	M135-M155	
Lamp Type	400W MH	
Number of Lamps	1 piece/unit	
Circuit Type	SUPER-CWA	
Ballast Type	Magnetic HID	
Base Model	71A6042TAEE	
Core Size	4 1/4 x 4 3/4 (2 coil)	
Suitable For Outdoor Use	Yes	
Ignitor Catalog Number	LI533-H4	
Ignitor Temperature Rating	105°C	
Capacitor Value	26 MFD	
Capacitor Catalog Number	7C260P33R	
Capacitor Requirements	330V	
Capacitor Temperature Rating	105°C	
Capacitor Diameter/Oval Dimensions	1.75 in	
Capacitor Height	4.80 in	
Automatic Restart	No	

Operating and Electrical	
Input Voltage	480/120T V
Input Frequency	60 Hz
Input Current (Open Circuit)	0.7 A
Input Current (Starting)	0.75 A
Input Current (Short Circuit)	0.5-0.8 A
Secondary Short Circuit Current	3.6-4.4 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	270 V
Input Current (Nom)	1 A A
Input Power (Nom)	452 W
Rated Lamp Power	400 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes


Datasheet, 2019, February 12 data subject to change

### Core & Coil (71A) MH 175W - 450W

Max Ballast-Lamp Distance Remote Wiring 2'		
Approval and Application		
Open Circuit Voltage Test (Volts)	240-300 V	
Approval Marks	ULR CSA certificate EISA RoHS Compliant	
Temperature Marking	D	
UL Recognized	Yes	
Hipot Test (1 Minute)	2000 V	
Hipot Test (2 Seconds)	2500 V	
UL Insulation Class	H(180°C)	
UL Temperature Code	1029D	

Product Data	
Order product name	CORE & COIL HID MH BAL 400W M135/155
	480V/120T C&C
EAN/UPC - Product	781087075593
Order code	913710677102
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	913710677102
Net Weight (Piece)	5.784 kg

#### Dimensional drawing



MH BAL 400W M135/155 480V/120T C&C

 Product
 C1
 C2
 A1
 A2
 B1
 B2

 CORE & COIL HID 7IA6042510DTAEE
 3.90 in
 2.10 in
 4.8 in
 4.4 in
 4.3 in
 3.9 in



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.