



# Core & Coil (71A) MH 175W - 450W

### CORE & COIL HID MH BAL 200W M136 QUAD C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information					
ANSI Code	M136				
Lamp Type	200W MH				
Number of Lamps	1 piece/unit				
Circuit Type	SUPER-CWA				
Ballast Type	Magnetic HID				
Base Model	71A5692EE				
Core Size	3 X 4 (2 coil)				
Suitable For Outdoor Use	Yes				
Ignitor Catalog Number	LI533-H4				
Ignitor Temperature Rating	105°C				
Capacitor Value	15 MFD				
Capacitor Catalog Number	7C150M33				
Capacitor Requirements	330V				
Capacitor Temperature Rating	105°C				
Capacitor Diameter/Oval	1.65 in				
Dimensions					
Capacitor Height	3.75 in				
Automatic Restart	No				

Operating and Electrical						
Input Voltage	120/208/240/277 V					
Input Frequency	60 Hz					
Input Current (Open Circuit)	1.85/1.06/0.91/0.8 A					
Input Current (Starting)	0.82/0.47/0.4/0.35 A					
Input Current (Short Circuit)	0.47-0.71/0.28-0.42/0.24-0.36/0.21-0.31 A					
Secondary Short Circuit Current	1.95-2.4 A					
Constant Wattage Deviation	10%					
Ballast Factor (Nom)	1					
Power Factor (Nom)	0.90					
Open Circuit Voltage	240 V					
Input Current (Nom)	2.12/1.22/1.06/0.93 A A					
Input Power (Nom)	227 W					
Rated Lamp Power	200 W					
Wiring						
Wire Striplength	0.5 mm					
Wire Length by Color	12"					
Wire Type	Stranded					
Remote Wiring Configuration	Yes					
Allowed						


Datasheet, 2019, February 12 data subject to change

## Core & Coil (71A) MH 175W - 450W

Max Ballast-Lamp Distance Remote	2'
Wiring	
Recommended Fuse Value	6/4/3/3 A
Approval and Application	
Open Circuit Voltage Test (Volts)	225-265 V
Approval Marks	ULR CSA certificate EISA RoHS Compliant
Temperature Marking	A/A/A/A
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)

UL Temperature Code	1029A
Product Data	
Order product name	CORE & COIL HID MH BAL 200W M136 QUAD C&C
EAN/UPC - Product	781087075999
Order code	913710677802
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	913710677802
Net Weight (Piece)	4.372 kg

#### Dimensional drawing



Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A5692510DEE	4.20 in	2.95 in	3.9 in	3.5 in	2.8 in	2.4 in

