



Core & Coil (71A) MH 175W - 450W

CORE & COIL HID MH BAL 175W M137/152 QUAD C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information				
ANSI Code	M137-M152			
Lamp Type	175W MH			
Number of Lamps	1 piece/unit			
Circuit Type	SUPER-CWA			
Ballast Type	Magnetic HID			
Base Model	71A5593EE			
Core Size	3 X 4 (2 coil)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI533-H4			
Ignitor Temperature Rating	105°C			
Capacitor Value	11 MFD			
Capacitor Catalog Number	7C110M40			
Capacitor Requirements	370V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval	1.65 in			
Dimensions				
Capacitor Height	3.75 in			
Automatic Restart	No			

120/208/240/277 V				
60 Hz				
2.0/1.16/1.15/0.85 A				
0.5/0.28/0.22/0.2 A				
0.4-0.6/0.23-0.34/0.17-0.26/0.16-0.25 A				
1.6-1.96 A				
10%				
1				
0.90				
285 V				
1.78/1.08/0.89/0.76 A A				
208 W				
175 W				
0.5 mm				
12"				
Stranded				


Datasheet, 2019, February 12 data subject to change

Core & Coil (71A) MH 175W - 450W

Remote Wiring Configuration	Yes			
Allowed				
Max Ballast-Lamp Distance	2'			
Remote Wiring				
Recommended Fuse Value	5/3/3/2 A			
Approval and Application				
Open Circuit Voltage Test (Volts)	250-300 V			
Approbation Marks	ULR CSA certificate EISA RoHS Compliant			
Temperature Marking	A/A/A/A			
UL Recognized	Yes			
Hipot Test (1 Minute)	2000 V			
Hipot Test (2 Seconds)	2500 V			
UL Insulation Class	H(180°C)			

UL Temperature Code	1029A
Product Data	
Order product name	CORE & COIL HID MH BAL 175W M137/152 QUAD
	C&C
EAN/UPC - Product	781087076170
Order code	71A5593510DEE
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	913710679202
Net Weight (Piece)	4.632 kg

Dimensional drawing



MH BAL 175 M137/152 QUAD C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A5593510DEE	4.41 in	3.20 in	3.9 in	3.5 in	2.8 in	2.4 in

