



SmartMate

SMARTMATE ELE BALLAST (3) 40W CFL (4-PIN) 120-277V

Offering maximum versatility, the Philips Advance family of SmartMate ballasts for 4-pin compact fluorescent lamps drive a broad range of quad and triple-tube, circline, 2D, and long twin-tube lamps. SmartMate ballasts' energy efficient design, compact and lightweight housing, and user-friendly features make these ballasts an ideal choice for fixture manufacturers, retrofitters, and MRO replacement.

Product data

General Information			
Lamp Type	FT40W/2G11		
Number of Lamps	2/3 piece/unit		
Ballast Type	Electronic Fluorescent		
Base Model	ICN3TTP40SC		
Suitable For Outdoor Use	Yes		
Automatic Restart	Yes		
Operating and Electrical			
Input Voltage	120 to 277 V		
Input Frequency	50 to 60 Hz		
Max THD	10 %		
Starting Method	Instant Start		
Lamp Current Crest Factor (Nom)	1.7		
Ignition Time (Nom)	0.1 s		
Ballast Factor (Nom)	0.88		
Power Factor (Nom)	0.98		
Input Current (Operating) (Max)	0.83 A		
Input Current (Operating) (Min)	0.35 A		
Input Power (Nom)	99-97 W		


Rated Lamp Watts	40 W			
Wiring				
Color Input Terminals	No terminals			
Color Output Terminals	No terminals			
Wire Striplength	0.50/0.375 mm			
Lamp Connection	Parallel			
Wire Length by Color	See data sheet			
Wire Gauge (Nom)	18AWG mm			
Wire Type	Solid			
Remote Wiring Configuration Allowed	Yes			
Tandem Wiring Configuration Allowed	Yes			
Through Wiring Configuration Allowed	Yes			
Max Ballast-Lamp Distance Remote Wiring	20'			
Max Ballast-Lamp Distance Tandem Wiring Any = 20'				
Max Ballast-Lamp Distance Through Wiring Any = 20'				
Connector Type	No connector			
Temperature				
T-Case Maximum (Nom)	70 ℃			

SmartMate

Mechanical and Housing			
Housing Material	Metal		
Housing	SC		
Housing Dimensions	9.5" x 1.7" x 1.18"		
Approval and Application			
EMC Immunity Standard	FCC Non-Consumer		
Approbation Marks	CSA certificate UL certificate CEC Listing		
	RoHS Compliant		
Sound Rating	A		
UL Recognized	No		

SMARTMATE ELE BALLAST (3) 40W CFL
(4-PIN) 120-277V
781087065099
ICN3TTP40SC35I
1
10
913710835401
0.568 kg

Dimensional drawing



Product	A1	A2	B1	C1
SMARTMATE ELE BALLAST (3) 40W CFL (4-PIN)	9.5 in	8.90 in	1.7 in	1.18 in
120-277V				



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.