



SmartMate

SMARTMATE ELE BALLAST (3) 40W CFL (4-PIN) 120-277V

Offering maximum versatility, the Philips Advance family of SmartMate ballasts for 4-pin compact fluorescent lamps drive a broad range of quad and triple-tube, circline, 2D, and long twin-tube lamps. SmartMate ballasts' energy efficient design, compact and lightweight housing, and user-friendly features make these ballasts an ideal choice for fixture manufacturers, retrofitters, and MRO replacement.

Product data

General Information		
Lamp Type	FT40W/2G11	
Number of Lamps	2/3 piece/unit	
Ballast Type	Electronic Fluorescent	
Base Model	ICN3TTP40SC	
Suitable For Outdoor Use	Yes	
Automatic Restart	Yes	
Operating and Electrical		
Input Voltage	120 to 277 V	
Input Frequency	50 to 60 Hz	
Max THD	10 %	
Starting Method	Instant Start	
Lamp Current Crest Factor (Nom)	1.7	
Ignition Time (Nom)	0.1 s	
Ballast Factor (Nom)	0.88	
Power Factor (Nom)	0.98	
Input Current (Operating) (Max)	0.83 A	
Input Current (Operating) (Min)	0.35 A	
Input Power (Nom)	99-97 W	

Rated Lamp Watts	40 W
Wiring	
Color Input Terminals	No terminals
Color Output Terminals	No terminals
Wire Striplength	0.50/0.375 mm
Lamp Connection	Parallel
Wire Length by Color	See data sheet
Wire Gauge (Nom)	18AWG mm
Wire Type	Solid
Remote Wiring Configuration Allowed	Yes
Tandem Wiring Configuration Allowed	Yes
Through Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	20'
Max Ballast-Lamp Distance Tandem Wiring	Any = 20'
Max Ballast-Lamp Distance Through Wiring	Any = 20'
Connector Type	No connector
Temperature	
T-Case Maximum (Nom)	70 °C


Datasheet, 2019, March 22 data subject to change

SmartMate

Metal		
SC		
9.5" x 1.7" x 1.18"		
FCC Non-Consumer		
CSA certificate UL certificate CEC Listing		
RoHS Compliant		
А		
No		

Product Data				
Order product name	SMARTMATE ELE BALLAST (3) 40W CFL			
	(4-PIN) 120-277V			
EAN/UPC - Product	781087065099			
Order code	ICN3TTP40SC35M			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	20			
Material Nr. (12NC)	913710835402			
Net Weight (Piece)	0.577 kg			

Dimensional drawing



ELE BALLAST (3) 40W CFL (4-PIN) 120-277V

Product	A1	A2	B1	C1
SMARTMATE ELE BALLAST (3) 40W CFL (4-PIN)	9.5 in	8.90 in	1.7 in	1.18 in
120-277V				

