



# e-Vision Low Wattage 20-150W

## E-VISION ELE MH BAL 20W M156 120-277V 50/60HZ

Low frequency electronic HID ballasts such as the Philips Advance e-Vision line constantly measure and adjust the wattage, optimizing delivery of the ceramic lamps' superior color properties. This makes ceramic metal halide operated by e-Vision ballasts the premier choice for many applications previously illuminated by either tungsten halogen or incandescent sources, such as retail lighting.

### Product data

General Information	
ANSI Code	C156-M156
Lamp Type	20W MH
Number of Lamps	1 piece/unit
Ballast Type	Electronic HID
Base Model	IMHG20ELF
Suitable For Outdoor Use	Yes
Operating and Electrical	
Input Voltage	120 to 277 V
Input Frequency	50 to 60 Hz
Total Harmonic Distortion USA	15 %
Crestfactor (Nom)	1.8
Ignition Time (Nom)	1200 s
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Input Current (Max)	0.21 A
Input Current (Min)	9.0 A

Input Power (Nom)	24 W
Rated Lamp Power	20 W
Wiring	
Color Input Terminals	No terminals
Color Output Terminals	No terminals
Wire Striplength	0.50 mm
Control Wire Gauge	NA
Wire Length by Color	All leads = 11"
Wire Gauge (Nom)	18AWG mm
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes
Tandem Wiring Configuration Allowed	No
Through Wiring Configuration Allowed	No
Connector Type	No connector

## e-Vision Low Wattage 20-150W

### Temperature

T-Case Maximum (Nom)	90 °C
----------------------	-------

### Mechanical and Housing

Housing Material	Metal
Housing	E
Housing Dimensions	5.0" x 1.7" x 1.2"


### Approval and Application

EMC Immunity Standard	FCC Non-Consumer
Approval Marks	CSA certificate UL certificate RoHS Compliant
Hum And Noise Level	A
UL Recognized	No

### Product Data

Order product name	E-VISION ELE MH BAL 20W M156 120-277V 50/60HZ
EAN/UPC - Product	781087076361
Order code	913710858902
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	913710858902
Net Weight (Piece)	0.234 kg

### Dimensional drawing



E-VISION IMHG20ELFM

Product	A1	A2	A3	A4	B1	B2	C1
E-VISION IMHG20ELFM	5.5 in	5.0 in	5.3 in	2.0 in	1.7 in	1.0 in	1.2 in

