



# Optanium T8 Instant Start

## OPTANIUM ELE BALLAST (3) F32T8 347V

Reliable and energy efficient Philips Advance's Centium commercial grade specifications, plus added benefits of lamp striation reduction technology.

### Product data


General Information	
Lamp type	F32T8
Number of lamps	2/3 piece/unit
Ballast type	Electronic Fluorescent
Base model	GOPA3P32SC
Suitable for outdoor use	Yes
Automatic restart	Yes
Operating and Electrical	
Input voltage	347 V
Input frequency	50 to 60 Hz
Total harmonic distortion USA	10 %
Ignition method	Instant Start
Crest factor (nom.)	1.6
Ignition time (nom.)	0.1 s
Ballast factor (nom.)	0.88
Power factor (nom.)	0.98
Input current (nom.)	0.24 A
Input power (nom.)	84 W
Rated lamp power	32 W
Wiring	
Colour input terminals	No terminals
Colour output terminals	No terminals
Wire strip length	0.50/0.375 mm
Lamp connection	Parallel
Wire length by colour	See data sheet
Wire gauge (nom.)	18AWG mm
Wire type	Solid
Remote wiring configuration allowed	Yes
Tandem wiring configuration allowed	Yes
Through-wiring configuration allowed	Yes
Max. ballast-lamp distance remote wiring	ES = 6' / Standard = 8'
Max. ballast-lamp distance tandem wiring	ES = 6' / Standard = 8'
Max. ballast-lamp distance through-wiring	ES = 6' / Standard = 8'
Connector type	No connector
Temperature	
T-Case maximum (nom.)	70 °C
Mechanical and Housing	
Housing material	Metal
Housing	SC

Optanium T8 Instant Start

Housing dimensions	9.5" x 1.7" x 1.18"
Approval and Application	
EMC immunity standard	FCC Non-Consumer
Approval marks	CSA certificate UL certificate CEE Rated RoHS Compliant
Humming and noise level	A
UL recognised	No
Product Data	
Order product name	OPTANIUM ELE BALLAST (3) F32T8 347V

EAN/UPC – product	781087081822
Order code	913710894702
Numerator – quantity per pack	1
Numerator – packs per outer box	20
Material no. (12NC)	913710894702
Net weight (piece)	0.441 kg

Dimensional drawing



Product	A1	A2	B1	C1
OPTANIUM ELE BALLAST (3) F32T8 347V	9.5 in	8.90 in	1.7 in	1.18 in

