



# PrimaVision Mini for CDM

## HID-PV m 1X020/S CDM LPF 220-240V

Miniature HID electronic gear for PGJ5 CDM lamps – freeing up the boundaries of creativity and innovation in luminaire design

### Product data

General Information	
Application code	LPF
Lamp type	CDM
Suitable for outdoor use	No
Number of products on MCB (16 A type B) (nom.)	36
Operating and Electrical	
Input voltage	220 to 240 V
Input frequency	50 to 60 Hz
Minimum mains voltage operation (min.)	198 V
Ignition voltage (max.)	1.4 kV
Ignition voltage (min.)	1.2 kV
Mains voltage performance (AC)	198-254V
Mains voltage safety (AC)	180-264V
Earth leakage current (max.)	0.25 mA
Inrush current width	0.4 ms
Constant wattage deviation	-3%/+3%
Inrush current peak (max.)	30 A


Wiring	
Cable capacity output wires mutual (nom.)	200 pF
System characteristics	
Rated ballast-lamp power	20 W
Temperature	
T ambient (max.)	50 °C
T ambient (min.)	-20 °C
T storage (max.)	80 °C
T storage (min.)	-25 °C
T case lifetime (nom.)	65 °C
T-Case maximum (max.)	75 °C
Mechanical and Housing	
Housing material	Plastic
Housing	/S
Approval and Application	
Active temperature protection	Yes
Vibration standard	IEC68-2-6 F c
Bumps standard	IEC 60068-2-29 Eb

## PrimaVision Mini for CDM

Approval marks	F-Marking CE marking VDE certificate
Humming and noise level	30 dB(A)
<b>Product Data</b>	
Full product code	871016306267900
Order product name	HID-PV m 1X020/S CDM LPF 220-240V
EAN/UPC – product	8710163149608

Order code	913712005214
Numerator – quantity per pack	1
Numerator – packs per outer box	12
Material no. (12NC)	913712005214
Net weight (piece)	0.199 kg

### Dimensional drawing



HID-PV m 1x020/S/S CDM LPF 220-240V

Product	D1	C1	A1	A2	B1
HID-PV m 1X020/S CDM LPF 220-240V	4.2 mm	30.5 mm	97.3 mm	88.3 mm	43.3 mm

