PHILIPS

Lighting



HID-CertaVision for CDM

HID-CV 35 /S CDM 220-240V

HID-CertaVision electronic ballast for use with ceramic metal-halide (CDM) lamps

Product data

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Inrush Current Width	0.28 ms
Inrush Current Peak (Nom)	22.4 A
Number of Products on MCB (16A Type B) (Nom)	24

Wiring	
Cable Length From Device to Lamp	2 m
Connector Type	Push

Temperature	
Ambient temperature range	-20 °C to 55 °C
T-Case Lifetime (Nom)	80 °C
T-Case Maximum (Max)	80 °C


Mechanical and Housing	
Housing	/S

Approval and Application	
Approval Marks	CE marking

Product Data	
Order product name	HID-CV 35 /S CDM 220-240V
Full product name	HID-CV 35 /S CDM 220-240V
Full product code	694793917416400
Order code	913712006580
Material Nr. (12NC)	913712006580
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6947939174164
Numerator - Packs per outer box	12
EAN/UPC - Case	6947939174171

HID-CertaVision for CDM

Dimensional drawing



Product	C1	A1	A2	B1	B2	B3
HID-CV 35 /S CDM 220-240V	32.1 mm	110.0 mm	98.5 mm	75.0 mm	63.7 mm	4.5 mm

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.