

EB-Certalume for TL5 lamps

EB-Ci 1-2 14-28W 220-240V 50/60 Hz

Affordable, reliable, high frequency electronic ballast for TL5 fluorescent lamps, ideal alternative for electromagnetic (EM) ballasts

Product data

Operating and Electrical	
Input Voltage	220-240 V
Input Frequency	50 or 60 Hz
Earth Leakage Current (Max)	0.5 mA
Inrush Current Width	0.224 ms
Inrush Current Peak (Max)	17 A
Number of Products on MCB (16A Type B) (Max)	30

Wiring	
Connector Type Input Terminals	Insert
Connector Type Output Terminals	Insert
Connector Type	Insert

Temperature	
T-Case Lifetime (Max)	75 °C
T-Case Maximum (Max)	75 °C


Mechanical and Housing	
Housing Material	Plastic
Housing	L210x30x26mm

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Energy Efficiency Index	A2
Safety Standard	IEC 61347-2-3,IEC 61347-1
Environmental Standard	ISO 14001
Approval Marks	CB Certificate CCC certificate TISI marking PSB certification RCM compliance SNI Certificate CS Compliance IRAM Compliance

Product Data	
Order product name	EB-Ci 1-2 14-28W 220-240V 50/60 Hz
Full product name	EB-Ci 1-2 14-28W 220-240V 50/60 Hz
Full product code	694793913355000
Order code	913713043280
Material Nr. (12NC)	913713043280
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6947939133550
Numerator - Packs per outer box	30
EAN/UPC - Case	6947939133567

EB-Certalume for TL5 lamps

Dimensional drawing



Product	A1	A2	B1	C1	D1
EB-Ci 1-2 14-28W 220-240V 50/60 Hz	210 mm	200 mm	30 mm	26 mm	4.3 mm

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.