



EB-Certalume for PLT/C lamps

EB-C 226 PL-T/C 220-240V 50/60Hz

Affordable, reliable, high frequency electronic ballast for 4-pin PL-T and PL-C fluorescent lamps, ideal alternative for electromagnetic (EM) ballasts

Product data


| Operating and Electrical | | | | | |
|-------------------------------------|---|--|--|--|--|
| Input Voltage | 220 to 240 V | | | | |
| Line Frequency | 50 to 60 Hz | | | | |
| Input Frequency | 50 to 60 Hz | | | | |
| Number of Products on MCB (16A Type | 20 | | | | |
| B) (Nom) | | | | | |
| | | | | | |
| Wiring | | | | | |
| Connector Type Input Terminals | 250 manual connector [Suitable for manual | | | | |
| | wiring and easy release button] | | | | |
| Color Input Terminals | Orange | | | | |
| Color Output Terminals | Grey | | | | |
| Connector Type Output Terminals | 250 manual connector [Suitable for manual | | | | |
| | wiring and easy release button] | | | | |
| | | | | | |
| Temperature | | | | | |
| T-Case Lifetime (Nom) | 65 ℃ | | | | |
| T-Case Maximum (Max) | 65 ℃ | | | | |
| | | | | | |
| Mechanical and Housing | | | | | |
| Housing | - [Not Specified] | | | | |
| | | | | | |

| Approval and Application | | | | |
|---------------------------------|----------------------------------|--|--|--|
| Ingress protection code | IP20 [Finger-protected] | | | |
| Energy Efficiency Index | A2 | | | |
| Approval Marks | CCC certificate CB Certificate | | | |
| | | | | |
| Product Data | | | | |
| Order product name | EB-C 226 PL-T/C 220-240V 50/60Hz | | | |
| Full product name | EB-C 226 PL-T/C 220-240V 50/60Hz | | | |
| Full product code | 872790088907900 | | | |
| Order code | 913713198914 | | | |
| Material Nr. (12NC) | 913713198914 | | | |
| Numerator - Quantity Per Pack | 1 | | | |
| EAN/UPC - Product/Case | 8711500998941 | | | |
| Numerator - Packs per outer box | 24 | | | |
| EAN/UPC - Case | 8727900889079 | | | |

Datasheet, 2023, April 15 data subject to change

EB-Certalume for PLT/C lamps

Dimensional drawing



| Product | D1 | C1 | A1 | A2 | B1 |
|----------------------------------|--------|---------|---------|---------|---------|
| EB-C 226 PL-T/C 220-240V 50/60Hz | 4.2 mm | 31.0 mm | 94.0 mm | 86.0 mm | 72.0 mm |

