

HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

BSN 70L 3011


The HID Basic Semi-Parallel ballast is an impregnated (HID standard) electromagnetic copper/iron ballast for use with an external ignitor for HID lamps.

Product data

General Information		Temperature	
Application Code	L301 I	T-Winding (Max)	130 °C
		Delta-T Normal Conditions	60 °C
Operating and Electrical		Product Data	
Input Voltage	220 V	Full product code	871829177078700
Input Frequency	60 Hz	Order product name	BSN 70L 3011
Power Factor 100% Load (Min)	0.35	EAN/UPC - Product	8718291770787
Mains Voltage Performance (AC)	-8% - +6%	Order code	913713206016
Mains Voltage Safety (AC)	-10% - +10%	Numerator - Quantity Per Pack	1
Input Current with PF Correction	0.45 A	Numerator - Packs per outer box	6
Input Current without PF Correction	0.98 A	Material Nr. (12NC)	913713206016
Power Factor without PF Compensation (Nom)	0.85	Net Weight (Piece)	1.010 kg
Power Losses (Nom)	10 W		
Wiring			
Connector Type	Screw		
System characteristics			
Rated Ballast-Lamp Power	70 W		

HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

Dimensional drawing



Product	D1	C1	A1	A2	B1
BSN 70L 301I	6.3 mm	51.5 mm	110.0 mm	89 mm	60.0 mm

BSN 70 L301 I

