



GreenPerform DN391/392/393/394/ 395 downlight

DN 395B LED 20S-3000 PSD WH

GreenPerform is a high performance Led downlight family suitable for use in a series of Lighting applications in Office, Retail and General Area Lighting. Available in a wide variety of lumen packs, color temp and options of all type of dimming(Phase Cut/Analogue/DALI), GreenPerform becomes the perfect solution for downlight applications for professional users.

Warnings and Safety

· Meant for use in Indoor environment only

Product data

General Information		Optical cover type
Driver included	Yes	Luminaire light bea
Light source engine type	LED	
Warranty period	3 years	Operating and E
Flammability mark	For mounting on normally flammable surfaces	Input Voltage
		Line Frequency
Light Technical		Power Consumptio
Luminous Flux	2,000 lm	Power Factor (Frac
Correlated Color Temperature (Nom)	3000 K	
Luminous Efficacy (rated) (Nom)	100 lm/W	Temperature
Color rendering index (CRI)	>80	Ambient temperate
Beam angle of light source	120 degree(s)	
Light source color	830 warm white	Controls and Dir
Optic type	-	Dimmable


Optical cover type	Polycarbonate
Luminaire light beam spread	120°
Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 Hz
Power Consumption	22 W
Power Factor (Fraction)	0.9
Temperature	
Ambient temperature range	0 to +45 °C
Controls and Dimming	
Dimmable	Yes

GreenPerform DN391/392/393/394/395 downlight

DALI
Aluminum Alloy
Polycarbonate
Polycarbonate
White
Spring clip for recess mounting
80 mm
185 mm
Aluminum
IP20 [Finger-protected]
IK02 [0.2 J standard]
2.5 kV
Safety class I

Initial Performance (IEC Compliant)		
Power consumption tolerance	+/-10%	
Over Time Performance (IEC Compliant)		
Median useful life L70B50	40,000 hour(s)	
Product Data		
Order product name	DN 395B LED 20S-3000 PSD WH	
Full product name	DN 395B LED 20S-3000 PSD WH	
Order code	919515810474	
Material Nr. (12NC)	919515810474	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	8	

Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, September 4 - data subject to change