



# GreenPerform DN391/392/393/394/ 395 downlight

## DN 394B LED16S-6500 PSU WH

GreenPerform is a high performance Led downlight family suitable for use in a series of Lighting applications in Office, Retail and General Area Lighting. Available in a wide variety of lumen packs, color temp and options of all type of dimming(Phase Cut/Analogue/DALI), GreenPerform becomes the perfect solution for downlight applications for professional users.

### Warnings and Safety

- Meant for use in Indoor environment only

### Product data

Light Technical		Temperature	
Correlated Color Temperature (Nom)	6500 K	Ambient temperature range	0 to +45 °C
Color rendering index (CRI)	>80		
Light source color	865 cool daylight	Controls and Dimming	
Luminaire light beam spread	110°	Dimmable	No
		Control interface	-
Operating and Electrical		Mechanical and Housing	
Input Voltage	220-240 V	Housing Material	Aluminum die cast
Line Frequency	50 Hz	Housing Color	White
Power Consumption	15.5 W	Overall height	80 mm
Power Factor (Fraction)	0.9	Overall diameter	185 mm
		Material	Aluminum

## GreenPerform DN391/392/393/394/395 downlight

### Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Surge Protection (Common/Differential)	2.5 kV
Protection class IEC	Safety class I

### Initial Performance (IEC Compliant)

Power consumption tolerance	+/-10%
-----------------------------	--------

### Product Data

Order product name	DN 394B LED16S-6500 PSU WH
Full product name	DN 394B LED16S-6500 PSU WH
Order code	919515810481
Material Nr. (12NC)	919515810481
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8

## Dimensional drawing

