



GreenPerform DN391/392/393/394/ 395 downlight

DN 395B LED20S-6500 PSU WH

GreenPerform is a high performance Led downlight family suitable for use in a series of Lighting applications in Office, Retail and General Area Lighting. Available in a wide variety of lumen packs, color temp and options of all type of dimming(Phase Cut/Analogue/DALI), GreenPerform becomes the perfect solution for downlight applications for professional users.

Warnings and Safety

· Meant for use in Indoor environment only

Product data

| General Information | |
|------------------------------------|---------------------------------------------|
| Driver included | Yes |
| Light source engine type | LED |
| Warranty period | 3 years |
| Flammability mark | For mounting on normally flammable surfaces |
| | |
| Light Technical | |
| Luminous Flux | 2,000 lm |
| Correlated Color Temperature (Nom) | 6500 K |
| Luminous Efficacy (rated) (Nom) | 100 lm/W |
| Color rendering index (CRI) | >80 |
| Beam angle of light source | 120 degree(s) |
| Light source color | 865 cool daylight |
| Optic type | - |
| | |

| Optical cover type | Polycarbonate | |
|-----------------------------|---------------|--|
| Luminaire light beam spread | 120° | |
| | | |
| Operating and Electrical | | |
| Input Voltage | 220-240 V | |
| Line Frequency | 50 Hz | |
| Power Consumption | 22 W | |
| Power Factor (Fraction) | 0.9 | |
| | | |
| Temperature | | |
| Ambient temperature range | 0 to +45 °C | |
| | | |
| Controls and Dimming | | |
| Dimmable | No | |


Datasheet, 2023, April 15 data subject to change

GreenPerform DN391/392/393/394/395 downlight

| Control interface | |
|----------------------------------------|---------------------------------|
| Control interface | |
| | |
| Mechanical and Housing | |
| Housing Material | Aluminum Alloy |
| Optic material | Polycarbonate |
| Optical cover material | Polycarbonate |
| Housing Color | White |
| Mounting device | Spring clip for recess mounting |
| Overall height | 80 mm |
| Overall diameter | 185 mm |
| Material | Aluminum |
| | |
| Approval and Application | |
| Ingress protection code | IP20 [Finger-protected] |
| Mech. impact protection code | IK02 [0.2 J standard] |
| Surge Protection (Common/Differential) | 2.5 kV |
| Protection class IEC | Safety class I |
| | |

| Initial Performance (IEC Compliant) | | |
|-------------------------------------|----------------------------|--|
| Power consumption tolerance | +/-10% | |
| | | |
| Over Time Performance (IEC Co | ompliant) | |
| Median useful life L70B50 | 40,000 hour(s) | |
| | | |
| Product Data | | |
| Order product name | DN 395B LED20S-6500 PSU WH | |
| Full product name | DN 395B LED20S-6500 PSU WH | |
| Order code | 919515810482 | |
| Material Nr. (12NC) | 919515810482 | |
| Numerator - Quantity Per Pack | 1 | |
| Numerator - Packs per outer box | 8 | |

Dimensional drawing







© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any $quotation\ or\ contract,\ unless\ otherwise\ agreed\ by\ Signify.\ Philips\ and\ the\ Philips\ Shield\ Emblem\ are\ registered$ trademarks of Koninklijke Philips N.V.