



# GreenPerform DN391/392/393/394/ 395 downlight

## DN 395B LED20S-4000 PSU WH

GreenPerform is a high performance Led downlight family suitable for use in a series of Lighting applications in Office, Retail and General Area Lighting. Available in a wide variety of lumen packs, color temp and options of all type of dimming(Phase Cut/Analogue/DALI), GreenPerform becomes the perfect solution for downlight applications for professional users.

#### Warnings and Safety

· Meant for use in Indoor environment only

#### Product data

General Information		Optical cover type
Driver included	Yes	Luminaire light bear
Light source engine type	LED	
Warranty period	3 years	Operating and Ele
Flammability mark	For mounting on normally flammable surfaces	Input Voltage
		Line Frequency
Light Technical		Power Consumption
Luminous Flux	2,000 lm	Power Factor (Fract
Correlated Color Temperature (Nom)	4000 K	
Luminous Efficacy (rated) (Nom)	100 lm/W	Temperature
Color rendering index (CRI)	>80	Ambient temperatur
Beam angle of light source	120 degree(s)	
Light source color	840 neutral white	Controls and Dim
Optic type	-	Dimmable


Optical cover type	Polycarbonate
Luminaire light beam spread	120°
Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 Hz
Power Consumption	22 W
Power Factor (Fraction)	0.9
Temperature	
Ambient temperature range	0 to +45 °C
Controls and Dimming	
Dimmable	No

### GreenPerform DN391/392/393/394/395 downlight

Control interface	-
Mechanical and Housing	
Housing Material	Aluminum Alloy
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Housing Color	White
Mounting device	Spring clip for recess mounting
Overall height	80 mm
Overall diameter	185 mm
Material	Aluminum
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Surge Protection (Common/Differential)	2.5 kV
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)		
Power consumption tolerance	+/-10%	
Over Time Performance (IEC Compliant)		
Median useful life L70B50	40,000 hour(s)	
Product Data		
Order product name	DN 395B LED20S-4000 PSU WH	
Full product name	DN 395B LED20S-4000 PSU WH	
Order code	919515810487	
Material Nr. (12NC)	919515810487	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	8	

#### Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, September 4 - data subject to change