



Greenbay BY400V

BY400V LED110S CW AK PSU S2 FG WH XTFC

GreenBay is an integrally designed, versatile lighting solution from Philips to address lighting application requirements within industrial spaces. From under canopies to truss mounted medium bay luminaires, GreenBay can be used in variety of recessed, surface or suspended mounted applications.

Product data

General Information	
Driver included	Yes
Light source engine type	LED
Warranty period	3 years
Flammability mark	For mounting on normally flammable surfaces
Light Technical	
Luminous Flux	11,000 lm
Correlated Color Temperature (Nom)	5700 K
Luminous Efficacy (rated) (Nom)	105 lm/W
Color rendering index (CRI)	>70
Beam angle of light source	35 degree(s)
Light source color	756 cool white
Optic type	Double asymmetric optic 35°
Optical cover type	Glass
Luminaire light beam spread	35°
Operating and Electrical	
Input Voltage	240 V
Line Frequency	50 Hz
Power Consumption	110 W
Power Factor (Fraction)	0.9

Temperature		
Ambient temperature range	0 to +45 °C	
Controls and Dimming		
Dimmable	No	
Mechanical and Housing		
Housing Material	Aluminum Alloy	
Optic material	Glass	
Optical cover material	Polycarbonate	
Housing Color	White	
Mounting device	Via U Shaped Bracket, Aiming Scale Angle,	
	Universal Installation	
Overall length	475 mm	
Overall width	365 mm	
Overall height	165 mm	
Dimensions (Height x Width x Depth)	165 x 365 x 475 mm	
Material	Aluminum	
Approval and Application		
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK07 [2 J reinforced]	
Surge Protection (Common/Differential) Surge protection level until 4 kV		

Datasheet, 2024, January 29 data subject to change


Greenbay BY400V

Protection class IEC	Safety class I	
Initial Performance (IEC Compliant)		
Power consumption tolerance	+/-10%	
Over Time Performance (IEC Compliant)		
Median useful life L70B50	50,000 hour(s)	
Product Data		
Order product name	BY400V LED110S CW AK PSU S2 FG WH XTFC	

Full product name	BY400V LED110S CW AK PSU S2 FG WH XTFC
Order code	919515811058
Material Nr. (12NC)	919515811058
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing







© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.