



Endura Next Batten

BN308C LED40S-6500 L120 IAO WH

With Philips Endura Next, customers have an industrial batten lighting solution that makes a valuable contribution to the profitability of their business, providing both operational and maintenance cost savings. By significantly reducing the energy consumption, this solution contributes to a lower carbon footprint. At the same time, the luminaire design ensures flicker free, consistent light output for the lifetime (50K hrs.), thereby guaranteeing the optimal working conditions for employees. It enhances productivity as well as takes care of safety of the employees. This unique solution comes with a wide range of intelligent (DALI, PIR movement detection) and networkable options such as Interact IoT enabled platform (both in Wired & Wireless options). No matter what your requirement is “Endura Next” comes with endless possibilities in this era of connected lighting and is specifically designed to minimize downtime in operations.

Warnings and Safety

- Meant for use in Indoor environment only

Product data

General Information		Light source color	
Driver included	Yes	Optic type	Beam angle 120°
Light source engine type	LED	Optical cover type	Polycarbonate
Warranty period	2 years	Luminaire light beam spread	120°
Flammability mark	For mounting on normally flammable surfaces	Operating and Electrical	
Light Technical		Input Voltage	140-270 V
Luminous Flux	4,000 lm	Line Frequency	50 Hz
Correlated Color Temperature (Nom)	6500 K	Power Consumption	34 W
Luminous Efficacy (rated) (Nom)	120 lm/W	Power Factor (Fraction)	0.95
Color rendering index (CRI)	>80		
Beam angle of light source	120 degree(s)		

Endura Next Batten

Temperature	
Ambient temperature range	0 to +45 °C
Controls and Dimming	
Dimmable	Wireless Dim
Control interface	InterAct office
Mechanical and Housing	
Housing Material	Steel
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Housing Color	White
Mounting device	Surface & Suspended (Asymmetric/ Symmetric)
Material	Steel
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Surge Protection (Common/Differential)	Surge protection level until 4 kV

Protection class IEC	Safety class I
Initial Performance (IEC Compliant)	
Initial chromaticity	<5
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compliant)	
Median useful life L70B50	50,000 hour(s)
Product Data	
Order product name	BN308C LED40S-6500 L120 IAO WH
Full product name	BN308C LED40S-6500 L120 IAO WH
Order code	919515812690
Material Nr. (12NC)	919515812690
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6

Dimensional drawing

