



# Reflector Flood

## 65BR30/FL55 CDA 130V

Philips Family of Specialty Incandescents provide the perfect light for dramatic accents and display lighting as well as general lighting in a variety of applications. These flood lamps produce homogeneous beams of high intensity for general illumination.

### Product data

| General Information          |   |
|------------------------------|---|
| Base                         | E26 [ Single Contact Medium Screw]  |
| Operating Position           | Universal [ Universal]  |
| Main Application             | Indoor Reflector  |
| Gas Filling                  | GAS   |
| Life with 3 Hour Per Day Use | 1.8 a   |
| Footnote Incandescent 1      | Consider the compact fluorescent lamps for energy savings.  |
| Footnote Incandescent 2      | Do not allow hot bulb to come in contact with liquid or metal parts of the fixture, as glass may shatter. Do not use outdoors. Do not operate in close proximity to flammable materials or those adversely affected by heat or drying. Operate only in heat resistant sockets. (87) |

| Light Technical                    |                |
|------------------------------------|----------------|
| Beam Angle (Nom)                   | 55 °           |
| Initial lumen (Nom)                | 605 lm         |
| Beam Description                   | Flood [ Flood] |
| Luminous Flux Lamp @ 120V          | 450 lm         |
| Correlated Color Temperature (Nom) | 2680 K         |

| Operating and Electrical |      |
|--------------------------|------|
| Power (Rated) (Nom)      | 65 W |

|                         |       |
|-------------------------|-------|
| Lamp Wattage Rated@120V | 55 W  |
| Voltage (Nom)           | 130 V |


| Mechanical and Housing |                            |
|------------------------|----------------------------|
| Bulb Finish            | Frosted (FR)               |
| Cap-Base Information   | Aluminium [ Aluminium Cap] |
| Filament Shape         | CC6 [ Straight]            |

| Approval and Application               |        |
|--|--------|
| Estimated Energy Cost Per Year at 120V | 6.67 S |
| Estimated Energy Cost Per Year         | 7.83 S |

| Product Data                    |                      |
|---------------------------------|----------------------|
| Order product name              | 65BR30/FL55 CDA 130V |
| EAN/UPC - Product               | 046677225209         |
| Order code                      | 248849               |
| Numerator - Quantity Per Pack   | 1                    |
| Numerator - Packs per outer box | 12                   |
| Material Nr. (12NC)             | 920681036112         |
| Net Weight (Piece)              | 0.001 kg             |

## Reflector Flood

### Dimensional drawing



#### Product

65BR30/FL55 CDA 130V

65W E26 130V BR30 FL FR

