



Standard Candle B35 clear

Stan 60W E14 240V B35 CL 1CT/10X10F

Flame-shaped bulb with clear glass and vacuum- or gas-filled bulb with B- or E-base $\,$

Product data


General Information Cap-Base E14 [E14] Operating Position UNIVERSAL [Any or Universal (U)] Nominal lifetime 1,000 hour(s) Rated Lifetime (Hours) 1,000 hour(s) Lighting Technology Incandescent Light Technical Luminous Flux 600 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 60 W Voltage (Nom) 240 V Voltage (Nom) 240 V Controls and Dimming Dimmable Yes		
Operating Position UNIVERSAL [Any or Universal (U)] Nominal lifetime 1,000 hour(s) Rated Lifetime (Hours) 1,000 hour(s) Lighting Technology Incandescent Light Technical Luminous Flux 600 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 60 W Voltage (Nom) 240 V Controls and Dimming	General Information	
Nominal lifetime 1,000 hour(s) Rated Lifetime (Hours) 1,000 hour(s) Lighting Technology Incandescent Light Technical Luminous Flux 600 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 60 W Voltage (Nom) 240 V Controls and Dimming	Cap-Base	E14 [E14]
Rated Lifetime (Hours) Lighting Technology Incandescent Light Technical Luminous Flux Gool Im Color rendering index (CRI) Operating and Electrical Power Consumption For Woltage (Nom) Voltage (Nom) 240 V Controls and Dimming	Operating Position	UNIVERSAL [Any or Universal (U)]
Light Technical Luminous Flux 600 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 60 W Voltage (Nom) 240 V Voltage (Nom) 240 V Controls and Dimming	Nominal lifetime	1,000 hour(s)
Light Technical Luminous Flux 600 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 60 W Voltage (Nom) 240 V Voltage (Nom) 240 V Controls and Dimming	Rated Lifetime (Hours)	1,000 hour(s)
Luminous Flux 600 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 60 W Voltage (Nom) 240 V Voltage (Nom) 240 V Controls and Dimming	Lighting Technology	Incandescent
Luminous Flux 600 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 60 W Voltage (Nom) 240 V Voltage (Nom) 240 V Controls and Dimming		
Color rendering index (CRI) 100 Operating and Electrical Power Consumption 60 W Voltage (Nom) 240 V Voltage (Nom) 240 V Controls and Dimming	Light Technical	
Operating and Electrical Power Consumption 60 W Voltage (Nom) 240 V Voltage (Nom) 240 V Controls and Dimming	Luminous Flux	600 lm
Power Consumption 60 W Voltage (Nom) 240 V Voltage (Nom) 240 V	Color rendering index (CRI)	100
Power Consumption 60 W Voltage (Nom) 240 V Voltage (Nom) 240 V		
Voltage (Nom) 240 V Voltage (Nom) 240 V Controls and Dimming	Operating and Electrical	
Voltage (Nom) 240 V Controls and Dimming	Power Consumption	60 W
Controls and Dimming	Voltage (Nom)	240 V
	Voltage (Nom)	240 V
Dimmable Yes	Controls and Dimming	
	Dimmable	Yes

Mechanical and Housing		
Bulb Finish	Clear	
Bulb Shape	B35 [B 35mm]	
Product Data		
Order product name	Stan 60W E14 240V B35 CL 1CT/10X10F	
Full product name	Stan 60W E14 240V B35 CL 1CT/10X10F	
Full product code	871016307586050	
Order code	921501045583	
Material Nr. (12NC)	921501045583	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8710163075860	
Numerator - Packs per outer box	100	
EAN/UPC - Case	8710163077499	

Datasheet, 2023, September 4 data subject to change

Standard Candle B35 clear

Dimensional drawing



Product	D	C (max)
Stan 60W E14 240V B35 CL 1CT/10X10F	35 mm	100 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.