



# HalogenA IDE

## HALA IDE 500W E40 230V CL 1CT/6

Mains-voltage high-wattage double-envelope giving a white halogen light


### Product data

General Information	
Cap base	E40 [E40]
Operating position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	2,000 h
Switching Cycle	8,000
Rated Lifetime (Hours)	2,000 h
Lighting Technology	Halogen
Light Technical	
Luminous Flux	10,250 lm
Correlated Colour Temperature	2900 K
Luminous efficacy (rated) (nom.)	20.5 lm/W
Colour rendering index (CRI)	100
Operating and Electrical	
Power Consumption	500.0 W
Lamp current (nom.)	2.17 A
Starting time (nom.)	0.0 s
Warm-up time to 60% light	Instant full light s
Power Factor (Fraction)	1
Voltage (nom.)	230 V
Voltage (nom.)	230 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Lamp Finish	Clear
Bulb shape	T38 [T 38 mm]
Approval and Application	
Energy consumption kWh/1,000 hours	500 kWh
Product Data	
Order product name	HaIA IDE 500W E40 230V CL 1CT/6
Full product name	HALA IDE 500W E40 230V CL 1CT/6
Full EOC	871150049126810
Order code	49126810
Material no. (12 NC)	923900144240
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8711500491268
Numerator – packs per outer box	6
EAN/UPC - Case	8711500499943

HalogenA IDE

Dimensional drawing



Product	D (max)	C (max)
HalA IDE 500W E40 230V CL 1CT/6	38.5 mm	216 mm

