



Halogen reflector

13158 150W GX5.3 21V 1CT

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

Product data

General Information		
Cap-Base	GX5.3 [GX5.3]	
Operating Position	S90 [Standing +/-90D or Base Down (BDH)]	
Life to 50% Failures (Nom)	40 hour(s)	
Light Technical		
Color rendering index (CRI)	100	
Operating and Electrical		
Power Consumption	150 W	
Voltage (Nom)	21 V	
Voltage (Nom)	21 V	
Controls and Dimming		
Dimmable	Yes	


Mechanical and Housing	
Bulb Material	Quartz-UV Open
Reflector Finish	Stippled
Bulb Shape	R50 [R 50mm]
Product Data	
Order product name	ELD 150W 21V 24PK

Product Data	
Order product name	ELD 150W 21V 24PK
Full product name	13158 150W GX5.3 21V 1CT
Full product code	871150041060330
Order code	41060330
Material Nr. (12NC)	923921319894
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500410603
Numerator - Packs per outer box	24
EAN/UPC - Case	8711500419040

Datasheet, 2023, May 1 data subject to change

Halogen reflector

Dimensional drawing



Product	D (max)	C (max)
ELD 150W 21V 24PK	50.7 mm	44.5 mm

