



MR11

FTD 20W GU4 12V MR11 30D CL 1CT/10X5F

Consistent color performance throughout lifetime. Philips Halogen MRC 11 Lamps Philips Halogen MRC11 Low-Voltage Reflector Lamps provide bright light for accent lighting.

Product data

General Information	
Cap-Base	GU4 [GU4]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	4,000 hour(s)
Switching Cycle	16,000
Rated Lifetime (Hours)	4,000 hour(s)
Lighting Technology	Halogen
Light Technical	
Beam Angle (Nom)	30 degree(s)
Luminous Flux	215 lumen
Correlated Color Temperature (Nom)	3000 K
Color rendering index (CRI)	100
Luminous Flux in 90° Cone (Rated)	215 lumen
Operating and Electrical	
Power Consumption	20.0 W
Lamp Current (Nom)	1.7 A
Starting Time (Nom)	0.0 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	1
Voltage (Nom)	12 V
Voltage (Nom)	12 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	MR11 [1.375inch/35mm]
Approval and Application	
Energy Consumption kWh/1000 h	21 kWh
Product Data	
Full product code	904667737822660
Order product name	FTD 20W GU4 12V MR11 30D CL 1CT/10X5F
Order code	924051317123
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	924051317123
Full product name	FTD 20W GU4 12V MR11 30D CL 1CT/10X5F
EAN/UPC - Case	50046677378221
EAN/UPC - Product/Case	046677378226

Dimensional drawing

Product	D (max)	C (max)
FTD 20W GU4 12V MR11 30D CL 1CT/10X5F	35 mm	40 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.