



HPL

7008 750W Heat Sink 115V 1CT/10

HPL lamps include a barrel-shaped filament that is approved by ETC for use in its Source Four $^{\text{TM}}$ fixtures. Bright, high quality light and high beam intensity is assured by the optimal filament design, while the unique P3 technology, developed by Philips, allows the lamp to be used at higher temperatures, which extends lifetime and consistency of high-quality light output, resulting in fewer early failures and fewer maintenance man hour costs.

Product data


General Information				
Cap-Base	HEATSINK [Heat Sink] UNIVERSAL [Any or Universal (U)]			
Operating Position				
Life to 50% Failures (Nom)	300 hour(s)			
Light Technical				
Color rendering index (CRI)	100			
Operating and Electrical				
Power Consumption	750 W			
Voltage (Nom)	115 V			
Voltage (Nom)	115 V			
Controls and Dimming				
Dimmable	Yes			

Clear				
871150018537225				
7008 750W Heat Sink 115V 1CT/10				
924555134428				
1				
10				
924555134428				
7008 750W Heat Sink 115V 1CT/10				
8711500185488				
8711500185372				

Datasheet, 2023, September 4 data subject to change

HPL

Dimensional drawing



Product	D (max)	Н	w	D1	L	C (max)
7008 750W Heat Sink 115V	19 mm	10.5 mm	6.3 mm	6.3 mm	60.3 mm	104 mm
1CT/10						

