



HPL

7008 750W/Heat Sink 230V 1CT/10

HPL lamps include a barrel-shaped filament that is approved by ETC for use in its Source Four $^{\text{TM}}$ fixtures. Bright, high quality light and high beam intensity is assured by the optimal filament design, while the unique P3 technology, developed by Philips, allows the lamp to be used at higher temperatures, which extends lifetime and consistency of high-quality light output, resulting in fewer early failures and fewer maintenance man hour costs.

Product data


General Information					
Cap-Base	HEATSINK [Heat Sink]				
Operating Position	UNIVERSAL [Any or Universal (U)]				
Life to 50% Failures (Nom)	300 hour(s)				
Light Technical					
Correlated Color Temperature (Nom)	3200 K				
Color rendering index (CRI)	100				
Operating and Electrical					
Power Consumption	750 W				
Voltage (Nom)	230 V				
Voltage (Nom)	230 V				
Controls and Dimming					
Dimmable	Yes				

Mechanical and Housing					
Bulb Finish	Clear				
Product Data					
Full product code	871150049658425				
Order product name	7008 750W/Heat Sink 230V 1CT/10				
Order code	924555144228				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	10				
Material Nr. (12NC)	924555144228				
Full product name	7008 750W/Heat Sink 230V 1CT/10				
EAN/UPC - Case	8711500496850				
EAN/UPC - Product/Case	8711500496584				

Datasheet, 2023, September 4 data subject to change

HPL

Dimensional drawing



Product	D (max)	Н	W	D1	L	C (max)
7008 750W/Heat Sink 230V	19 mm	11.5 mm	8.6 mm	7.5 mm	60.3 mm	104 mm
1CT/10						

