



Hi-Brite

7015 TXO 10PK


The compact, shock-resistant design of the Hi-Brite lamp series makes it easy to handle and ideal for moving head systems. Also, the compact filament ensures a high beam intensity, which can be used to reduce energy consumption: for example, 1200W can now be used instead of 2500W. In addition, the highly innovative P3 technology, developed by Philips, allows the lamp to be used at higher temperatures in any burning position, which further extends lamp lifetime, reduces lamp replacement costs and ensures consistency of high-quality light output.

Product data

General Information	
Cap-Base	GX9.5 [GX9.5]
Operating Position	UNIVERSAL [Any or Universal (U)]
Life to 50% Failures (Nom)	300 hour(s)
Light Technical	
Correlated Color Temperature (Nom)	3200 K
Color rendering index (CRI)	-
Operating and Electrical	
Power Consumption	750 W
Voltage (Nom)	100 V
Voltage (Nom)	100 V
Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Clear
Product Data	
Order product name	7015TXO 750W GX9.5 100V 1CT/10
Full product name	7015 TXO 10PK
Full product code	871150050557625
Order code	151795
Material Nr. (12NC)	924574530928
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500505576
Numerator - Packs per outer box	10
EAN/UPC - Case	8711500505583

Dimensional drawing



Product	D (max)	H	W	L	C (max)
7015TXO 750W GX9.5 100V 1CT/10	19 mm	8.5 mm	9.5 mm	55 mm	104 mm

