



Halogen FastFit

GRT 800/230 Fast Fit

Halogen FastFit lamps are replaced in seconds - thanks to the specially designed base. The compact filament ensures high beam intensity, while the shock-resistant design allows easy handling and reliable use in moving head systems. In addition, the highly innovative P3 technology allows use at higher temperatures, which further extends lifetime and consistency of light output. P3 technology also allows the lamp to be used in any burning position and enables more compact designs of fixtures. And because the FastFit design is also applied to Philips MSR/MSD Gold™ lamps, switching lamp technologies is also quick and easy.


Product data

General Information	
Base	PGJX50 [PGJX50]
Philips Code	7018G
ANSI Code	GRT
Operating Position	Universal [Universal]
Main Application	Entertainment
Life to 50% Failures (Nom)	150 h
System Description	P3 Technology
Light Technical	
Luminous Flux (Rated) (Nom)	20000 lm
Correlated Color Temperature (Nom)	3200 K
Operating and Electrical	
Power (Rated) (Nom)	800 W
Rapid Acting HBC Fuse	6.3 V
Voltage (Nom)	230 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear (CL)
Filament Shape	Bi-Plane
Filament Dimensions WxH	9x12.5
Luminaire Design Requirements	
Pinch Temperature (Max)	500 °C
Product Data	
Order product name	7018G 800W PGJX50 230V FastFit
EAN/UPC - Product	8727900807370
Order code	229096
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	924582344228
Net Weight (Piece)	0.130 kg

Halogen FastFit

Dimensional drawing



7018G 800W 230V FastFit

Product	D (max)	H	W	L	C (max)	E (max)
7018G 800W PGJX50 230V FastFit	19 mm	12.5 mm	9 mm	79 mm	140 mm	41 mm

