



# **Halogen FastFit**

## **GRT 800/230 Fast Fit**

Halogen FastFit lamps are replaced in seconds – thanks to the specially designed base. The compact filament ensures high beam intensity, while the shock-resistant design allows easy handling and reliable use in moving head systems. In addition, the highly innovative P3 technology allows use at higher temperatures, which further extends lifetime and consistency of light output. P3 technology also allows the lamp to be used in any burning position and enables more compact designs of fixtures. And because the FastFit design is also applied to Philips MSR/MSD Gold™ lamps, switching lamp technologies is also quick and easy.

#### **Product data**


General Information					
Cap-Base	PGJX50 [PGJX50]				
Operating Position	UNIVERSAL [Any or Universal (U)]				
Life to 50% Failures (Nom)	150 hour(s)				
Light Technical					
Correlated Color Temperature (Nom)	3200 K				
Operating and Electrical					
Power Consumption	800 W				
Voltage (Nom)	230 V				
Voltage (Nom)	230 V				
Controls and Dimming					
Dimmable	Yes				

Mechanical and Housing					
Bulb Finish	Clear				
Product Data					
Order product name	7018G 800W PGJX50 230V FastFit				
Full product name	GRT 800/230 Fast Fit				
Full product code	872790080737000				
Order code	229096				
Material Nr. (12NC)	924582344228				
Numerator - Quantity Per Pack	1				
EAN/UPC - Product/Case	8727900807370				
Numerator - Packs per outer box	10				
EAN/UPC - Case	8727900807387				

Datasheet, 2023, May 1 data subject to change

## Halogen FastFit

### Dimensional drawing



Product	D (max)	н	W	L	C (max)	E (max)
7018G 800W PGJX50 230V FastFit	19 mm	12.5 mm	9 mm	79 mm	140 mm	41 mm

