



Halogen PAR

70PAR38/EV/FL25/LL 120V 6/2 TP

Halogen PAR lamps reduce energy consumption without sacrificing the qualities of a traditional PAR lamp. They uniquely produce light more efficiently. They work with dimmer switches and are available in the familiar PAR20, PAR30S, PAR30L, and PAR38 shapes. Use them in existing fixtures just as you would standard halogen PAR lamps.


Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Operating Position	UNIVERSAL [Any or Universal (U)]
Rated Lifetime (Hours)	4,200 hour(s)
Lighting Technology	Halogen
Light Technical	
Beam Angle (Nom)	25 degree(s)
Luminous Flux (Max)	1,500 lm
Luminous Flux	1,415 lm
Luminous Intensity (Nom)	6,170 cd
Color rendering index (CRI)	100
Operating and Electrical	
Power Consumption	70 W
Voltage (Nom)	120 V
Voltage (Nom)	120 V

Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Hard Glass
Reflector Finish	Aluminized
Bulb Shape	PAR38 DiOptic
Product Data	
Order product name	70PAR38/EV/FL25/LL 120V 6/2 TP
Full product name	70PAR38/EV/FL25/LL 120V 6/2 TP
Order code	924757119808
Material Nr. (12NC)	924757119808
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677421335
Numerator - Packs per outer box	6
EAN/UPC - Case	50046677430424

Halogen PAR

Dimensional drawing



Product	D	C (max)
70PAR38/EV/FL25/LL 120V 6/2 TP	4.75 inch	5.313 inch

