



Energy Advantage IR PAR30

Energy Advantage IR 55PAR30S/IRC+/FL25 120V 15/1

Due to the heat that radiates from the bulb, a minimum distance of 2 ft is required between bulb and combustible materials or objects susceptible to drying or fading

Product data

General Information	
Base	E26 [Single Contact Medium Screw]
Operating Position	Universal [Universal]
Main Application	Flood and Ambient Lighting
Gas Filling	GAS
Life with 3 Hour Per Day Use	3.8 a
Light Technical	
Beam Angle (Nom)	25 °
Initial lumen (Nom)	1020 lm
Luminous Intensity (Nom)	3300 cd
Beam Description	Flood [Flood]
Correlated Color Temperature (Nom)	2760 K
Color Rendering Index (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	55 W
Voltage (Nom)	120 V
Mechanical and Housing	
Bulb Finish	Clear (CL)

Cap-Base Information	Brass [Brass Cap]
Bulb Material	Hard Glass
Reflector Finish	Aluminized
Filament Shape	CC-8 [Axial]


Approval and Application	
Estimated Energy Cost Per Year	6.62 \$

Product Data	
Order product name	Energy Advantage IR 55PAR30S/IRC+/FL25 120V 15/1
EAN/UPC - Product	046677238568
Order code	238568
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	15
Material Nr. (12NC)	924757122501
Net Weight (Piece)	190.000 g

Energy Advantage IR PAR30

Dimensional drawing

Product	D	C (max)
Energy Advantage IR 55PAR30S/IRC+/FL25 120V 15/1	3.75 in	3.625 in



PAR30 IRC 55W E26/Brass 120V FL 25D CC-8

