



PAR56 and PAR64

PAR64 1000W 240V NSP

These self-contained spotlights are ideal for intensifying the visual experience in all kinds of clubs, that is because their accurate beam control picks out even the smallest of details even over long distances. This beam control makes the PAR 56 and PAR 64 excellent for long-range light projections. In addition, the universal burning feature provides complete flexibility of luminaires angle and position, while the front glass of the PAR56 provides thermal and physical protection. The result? Complete creative freedom to achieve the desired effect. Immediate re-strike also ensures instant resumption of entertainment after any power interruption.


Product data

| General Information | |
|--------------------------------------|----------------------------|
| Cap base | GX16D [GX16d] |
| ANSI Code | EXD |
| LIF code | CP61 |
| Operating position | UNIVERSAL [Any/Universal] |
| Main application | Flood and Ambient Lighting |
| Gas filling | GAS |
| Life to 50% failures (min.) | 300 h |
| Nominal lifetime (nom.) | 300 h |
| Light Technical | |
| Beam Angle (Nom) | 12 ° |
| Luminous intensity (max.) | 290000 cd |
| Beam description | Narrow Spot |
| Correlated colour temperature (nom.) | 3200 K |
| Operating and Electrical | |
| Power (Rated) (Nom) | 1000 W |
| Voltage (Nom) | 240 V |

| Controls and Dimming | |
|---------------------------------|----------------------|
| Dimmable | yes |
| Mechanical and Housing | |
| Cap base information | na [-] |
| Product Data | |
| Full product code | 871150044072310 |
| Order product name | PAR64 1000W 240V NSP |
| EAN/UPC – product | 8711500440723 |
| Order code | 44072310 |
| Numerator – quantity per pack | 1 |
| Numerator – packs per outer box | 6 |
| Material no. (12NC) | 924783345504 |
| Net weight (piece) | 0.760 kg |

PAR56 and PAR64

Dimensional drawing



PAR64 1000W 240V NSP

| Product | D (max) | C (max) |
|----------------------|---------|---------|
| PAR64 1000W 240V NSP | 204 mm | 150 mm |

