



Capsuleline

CAPS 10W G4 12V CL 2000H 1CT/10X10F

Low-voltage halogen capsule. Ideal solution for small decorative luminaires. UV-block glass and low-pressure filling allow usage without cover glass. The compact Capsuleline delivers crisp white light over a long lifetime.

Product data

General Information	
Cap base	G4 [G4]
Philips code	18182
Operating position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime (nom.)	2000 h
Switching cycle	8000X

Light Technical	
Luminous flux (nom.)	100 lm
Luminous flux (rated) (nom.)	100 lm
Correlated colour temperature (nom.)	2700 K
Luminous efficacy (rated) (nom.)	10 lm/W
Color rendering index (nom.)	100
LLMF at end of nominal lifetime (min.)	80 %

Operating and Electrical	
Power (Rated) (Nom)	10.0 W
Lamp current (nom.)	0.83 A
Starting time (nom.)	0.0 s
Warm-up time to 60% light (nom.)	instant full light
Power factor (nom.)	1
Voltage (Nom)	12 V

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb finish	Clear (CL)
Cap base information	na [-]

Approval and Application	
Energy efficiency label (EEL)	C
Energy Consumption kWh/1000 h	11 kWh

Luminaire Design Requirements	
Bulb temperature (max.)	220 °C
Pinch temperature (max.)	350 °C


Product Data	
Full product code	871150041298050
Order product name	Capsuleline 10W G4 12V CL 2000h 1CT/10X10F
EAN/UPC – product	8711500412980
Order code	41298050
Numerator – quantity per pack	1
Numerator – packs per outer box	100
Material no. (12NC)	924891917110
Net weight (piece)	0.002 kg

Capsuleline

ILCOS Code

HSG/C/UB-10-12-G4

Dimensional drawing



Product	D (max)	L	C (max)
Capsuleline 10W G4 12V CL 2000h 1CT/10X10F	10 mm	22.2 mm	33 mm

CAP Fighter 18182 10W G4 12V CL

